TECHNICAL DESCRIPTION EPSON SURELAB D3000 DR - PROMO II - PRINTER

General	Printer type		Photo printer - inkjet / do	ot matrix - 9 pin - color
Printer	Inkjet printer technology		Epson Micro Piezo	
	Supported ink palette (colors)		6 inks - cyan, magenta, yellow, black, light cyan, light magenta	
	Minimum ink droplet size		1.5 pl	
	Configuring the ink ca	rtridge	6 individual ink tanks	
	Ink type		Epson UltraChrome D6	Ink
Printing speed			Up to 10.8 ppm - 100 x	150 mm
	Connectivity technology		wired	
	Interface		USB 2.0	
	Maximum resolution (B&W)		1440 x 1440 dpi	
	Maximum resolution (color)		1440 x 1440 dpi	
	Printer features		Auto Nozzle Check System	
Support management	Type of supports		Continuous paper, glossy paper, matte paper	
	Max. Size support		Roll (30.5 cm x 100 m)	
	Minimum media size (custom)		100 mm x 90 mm	
	Maximum media size (custom)		300 mm x 1220 mm	
	Recognized standard formats		Roll (25.4 cm), Roll (10.2 cm), Roll (12.7 cm), Roll (30.5 cm), Roll (20.3	
	Maximum printing width		307 mm	
	Total capacity		2 rolls	
	Media entries		1 x automatic - 1 tilt - Roll (30.5 cm x 100 m) ¿1 x automatic - 1 tilt - A4	
Expansion / Connectivity	connections		1 x USB 2.0 - 4-pin USB type B	
	Various	Included accessories		Rear printing unit, cleaning sheets, Humidity c Unit
	Consumal		bles included	1 x ink cartridge (black) ¿1 x ink cartridge (cya (yellow) ¿1 x ink cartridge (light cyan) ¿1 x ink ribbon
Food	d Power Device		Power supply - internal	
	Voltage required		AC 120/230 V	
	Frequency required		50/60 Hz	
	Consumption in operation		600 Watt	
Manufacturer's warranty	Service and maintenance		Limited warranty - 1 year	r - on site
	Environmental	Minimum operating temperature		10 ° C
	characteristics	Maximum operating temperature		35 ° C
		Operating humidity		5 - 85% (non-condensing)

Sound emission (active)

60 dBA

Dimensions and weights

Width	85 cm
Depth	1150 cm
Height	73 cm
Weight	127 kg