

---

<b>Printing Method</b>	Epson Micro Piezo drop-on-demand inkjet technology, High-performance print head technology designed for robust printing environments, Variable Sized Droplet Technology
<b>Printing Resolution</b>	720x720dpi on Lustre Paper, 720x720dpi on Glossy Paper, 1440x1440dpi on Matte Paper, 1440x1440dpi on Lustre Paper, 1440x1440dpi on Glossy Paper
<b>Minimum Droplet Size</b>	1.5 pl, With Variable-Sized Droplet Technology
<b>Max. Print speed</b>	650 - 4x6" (10x15cm) Prints/h

---

## Ink

<b>Ink Technology</b>	Ultrachrome® D6
<b>Ink Set</b>	6 colours
<b>Available Colours</b>	Black, Cyan, Light Cyan, Light Magenta, Magenta, Yellow
<b>Cartridge Size</b>	700 ml

---

## Media

<b>Media Channels</b>	Glossy, Lustre, Matte
<b>Supported Media</b>	Glossy, Lustre, Matte
<b>Media Handling</b>	Rear roll up to 305mm/12-inch media width
<b>No. Of Roll holders</b>	1 pcs
<b>Rear Roll specs</b>	Max. Roll Length 100 m, Core Diameter 76 mm ( 3 inch ), External Diameter 265 mm, Weight < 8.5 kg
<b>Front Roll specs</b>	Max. Roll Length 100 m, Core Diameter 76 mm ( 3 inch ), External Diameter 265 mm, Weight < 7.5 kg

<b>Supported Media Width</b>	102mm (4-inch), 127mm (5-inch), 152mm (6-inch), 203mm (8-inch), 210mm (A4), 254mm (10-inch), 305mm (12-inch)
<b>Print Size</b>	10.2 cm x 8.9 cm to 30.5 cm x 121.9 cm, 4 inches x 3.5 inches to 12 inches x 48 inches
<b>Max. Print width</b>	307 mm
<b>Print Margins</b>	Border defined by application, Borderless
<b>Auto Cutter</b>	Yes

---

## General

<b>Optional Sorter</b>	Yes A4 sorter with 10 trays, long print ejection unit and tray for medium sized prints
<b>Back Print Unit</b>	Yes Dot matrix, 9pin: 40 characters x 2 lines
<b>Character Size</b>	Yes 7 x 9dot/1 character: 1.2 x 3.1mm
<b>Other Hardware</b>	Auto Nozzle Check System, Control Panel, Humidity Control Unit
<b>Environmental Conditions - Temperature</b>	Operating: 15 - 35 °C (except Matte), Matte: 15 - 25 °C, Storage: -20 - 40 °C
<b>Environmental Conditions - Humidity</b>	Operating 30 - 60 % (except Matte, no condensation), Storage 5 - 85 % (no condensation)
<b>Power Consumption</b>	Operating (approx.) 600 W
<b>Voltage</b>	100 V- 120 V, 220 V- 240 V, 50/ 60 Hz
<b>Humidity Control Unit</b>	Voltage: 3 V/ 6 A Power Consumption: average 3 W
<b>Available Software</b>	Printer Driver (standard bundling), System Application (standard bundling), Order Controller (optional)
<b>Sound Pressure Level</b>	< 60 dB (A) (ISO9296 Standard)
<b>Compatible Operating Systems</b>	Windows 7, Windows 8
<b>Interfaces</b>	Hi-Speed USB - compatible with USB 2.0 specification

<b>Product dimensions</b>	850 x 760 x 730 mm (Width x Depth x Height)
<b>Product weight</b>	119 kg
<b>What's in the box</b>	Back Print Unit, Cleaning Sheets, spectextoptionincludedaccessoriesdocumentpack, Humidity Control Unit, Ink set, Maintenance Tank, Paper band(s), Spindle Unit(s), Two Ribbon Cassettes, USB cable

---