

<b>Scanner type</b>	Sheetfed Scanner
<b>Optical Resolution (ADF)</b>	600 DPI x 600 DPI (Horizontal x Vertical)
<b>Scanning Resolution</b>	600 DPI x 600 DPI (Horizontal x Vertical)
<b>Scanning Range (maximum)</b>	215.9 mm x 3,048 mm (Horizontal x Vertical)
<b>Paper Formats</b>	A4, Letter Legal, A5, A6, B5, B6, Business cards, Postcard, Legal, Plastic cards
<b>Colour Depth</b>	Input: 16 Bits Colour , Output: 8 Bits Colour
<b>Application</b>	Small & Compact

---

## Scanner

<b>Optical Sensor</b>	CIS (Contact Image Sensor)
<b>Light Source</b>	ReadyScan LED technology
<b>Output Resolution</b>	600 DPI

---

## Scan speed

<b>Scanning Speed</b>	Monochrome: 26 pages/min - Color: 26 pages/min measured with size: A4 , resolution: 200 / 300 dpi
-----------------------	---

---

## Paper / Media Handling

<b>ADF Paper Setting Capacity</b>	50 Sheets
<b>ADF Paper weight</b>	Auto loading: 50 - 209 g/m <sup>2</sup> , Manual loading:50 - 209 g/m <sup>2</sup>
<b>Automatic Document Feeder Type</b>	Single pass dual scanning
<b>Reliability Daily Duty Cycle</b>	3,000 pages
<b>Automatic Document Feeder</b>	50 pages
<b>Duplex Scan</b>	Yes

---

## Scanning Features

<b>Features</b>	RGB colour dropout, Skip blank page, A3 stitching (without carrier sheet), Automatic de-skew, RGB colour enhance, Auto-rotation, Text enhancement, Barcode Recognition, Full Zonal OCR
<b>Output formats</b>	BMP, JPEG, TIFF, multi-TIFF, PDF, PNG

---

## Connectivity

<b>Interfaces</b>	USB 2.0 Type B
-------------------	----------------

---

## General

<b>Supply Voltage</b>	AC 100 V - 240 V, 50 Hz - 60 Hz
<b>Energy Use</b>	15 Watt (Operation), 4.1 Watt (ready), 0.6 Watt (sleep mode), 0.2 Watt (Power off)
<b>Product dimensions</b>	297 x 152 x 154 mm (Width x Depth x Height)
<b>Product weight</b>	2.5 kg
<b>Drivers</b>	TWAIN, WIA, ISIS
<b>Included Software</b>	Document Capture Pro 2.0, Epson Document Capture (Mac only), Epson Scan 2
<b>Compatible Operating Systems</b>	Mac OS 10.10.x, Mac OS 10.11, Mac OS 10.6+, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2003 R2 x64, Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows XP
<b>Humidity</b>	Operation 15% - 80%, Storage 15% - 85%
<b>Temperature</b>	Operation 5° C - 35° C, Storage 60° C - 25° C
<b>What's in the box</b>	CD Manual, Power cable, Setup guide, USB cable, Warranty card
<b>Options</b>	Roller Assembly Kit

---