Product Specifications

Title: TASKalfa 352ci

Output Up to 35 pages A4 per minute Speed: Duplex print speed: 17 page per

minute, A4

Processor: ARM Cortex-A9 Dual core 1.2GHz +

ARM Cortex-M3 100MHz

Resolution: 1200 x 1200 dpi print resolution

Memory: Standard 1GB, Max. 3GB + 128GB

SSD

First Copy

Time:

Approx. 8.5 sec (BW) / 10 sec (Colour)

Time To Print First Page:

Approx. 6 sec (BW) / 7.5 sec (Colour)

Warm Up Time:

Approx. 25 seconds or less

Paper Handling

250 sheet paper cassette + 100 sheet

multipurpose tray

Input:

1,850 sheets (with optional 3 x PF-5100

Paper

Paper Feeders)

Handling Input:

Maximum

250 sheets face down

Paper Handling Output:

Output Size: A4

Duplex: Standard (built-in)

HDD: Optional: HD-6 SSD (32GB) or HD-7

SSD (128GB)

Printing: Standard: Network Printing

Scanning: Scan-to-Email, Scan-to-FTP, Scan-to-

SMB, Scan to USB Host, Local/Network

TWAIN, WIA, WSD scan

Scan Speed: 62 ipm (300 dpi, A4, b/w), 46 ipm (300

dpi, A4 colour), 46 ipm (300 dpi, A4, b/w) (Duplex), 32 ipm (300 dpi, A4

colour) (Duplex)

ScanColour scan, integrated address book, **Features:** Active Directory support, encrypted

data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once, Blank

page skip

Faxing: ITU-T Super G3

Zoom: 25-400%, in 1% steps

Emulation: PCL6 (5c/XL), KPDL3 (PostScript 3

compatible), PDF Direct Print, XPS

Direct Print

Standard USB 2.0 (Hi-Speed), 2 x USB Host

Interface: Interface, Gigabit Ethernet

(10BaseT/100BaseTX/1000BaseT. IPv6, IPv4, IPSec, 802.3az support), optional Wi-Fi (IEEE 802.11b/g/n), 1 eKUIO slot for optional internal print server, Slot for optional SD Card

Control Panel:

177.8 mm (7 inch) full-colour touch

panel display, speaker for job

notification, 10° - 20° swivel mounted

200,000 pages **Drum Life:**

Optional: Data Security Kit (E): In line Security:

with ISO 15408 (Common Criteria) with

security level EAL2

Finishing Options:

Optional: MS-5100 B Stapler (20

sheets, one position)

Dimensions & (W x D x H): 480 x 577 x 619.5 mm

Weight: Approx. 36.5 kg

Warranty: 3 year on-site warranty - extended

warranty options are available

Additional Information: This unit is manufactured according to ISO 9001 quality standard and ISO

14001 environmental standard.

Please note: Use of this device by USB cable may limit the capabilities of the device. For more information please contact Kyocera on 13 59 62 (Australia)

or 0800 459 623 (New Zealand).