

|                                       |   |
|---------------------------------------|---|
| Technology                            | Kyocera TASKalfa Laser MFP  |
| Control Panel Type                    | 9" Color TSI  |
| Product Category                      | A3 Color MFP  |
| Functions (Print / Scan / Copy / Fax) | Print/Scan/Copy/Fax   |
| Engine Speed                          | 60 ppm B&W, 55 ppm Color  |
| Warm-up Time                          | 17 Seconds  |
| First Page Out Time (print/copy)      | Print: 3.8 Seconds B&W, 5.1 Seconds Color<br>Copy: 3.4 Seconds B&W, 4.4 Seconds Color |
| Resolution                            | 1200 x 1200 dpi   |
| Bit Depth                             | 8 Bit   |
| CPU                                   | Freescale QorIQ T1024 (Dual Core) / 1.2GHz  |
| Memory (std/max)                      | Standard: 4 GB RAM<br>Maximum: 4 GB RAM   |
| Hard Disk Drive (Standard / Optional) | Standard: 320 GB HDD and 8 GB SSD   |
| Electrical Requirements               | 120V: 60Hz, 12A; 220-240V: 50Hz, 7.2A   |
| Dimensions (W x D x H)                | 60.2 cm x 66.5 cm x 79 cm   |
| Mainframe Weight                      | 202.8 lbs   |
| Maximum Monthly Duty Cycle            | 250,000 Pages Per Month   |
| Maximum average monthly print volume  | NULL  |
| Power Consumption                     | Typical Electricity Consumption (TEC): 120V: 3.2 kWh/week;<br>220V: 3.1 kWh/week      |
| Input Capacity (std/max)              | Standard: 1,150 Sheets<br>Maximum: 7,150 Sheets                                       |
| Output Capacity (std / max)           | Standard: 500 Sheets<br>Maximum: 4,000 Sheets   |
| Paper Sources (std / max)             | Standard: 2 Trays + 1 MPT<br>Maximum: 5 Trays + 1 MPT                                 |
| Maximum Paper Size                    | 12" x 48"   |
| Supported Paper Weights               | Trays/MPT: 14 lb Bond - 166 lb Index  |

---

Input Materials

Plain Paper, Bond Paper, Recycled Paper, Envelopes,  
Cardstock, Transparencies, Labels

---

Standard Interface

10/100/1000BaseTX, Hi-Speed USB 2.0, 4 USB Host  
Interfaces, 2 Expansion Slots