

Printing Technology	Direct Thermal
Print Speed (maximum)	6 inches per second (150 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	0.5 to 4 inches (12.5 to 118 mm)
Media Thickness (min to max)	63.5 to 254 µm
Media Sensor	Fully adjustable gap, notch and reflective black mark
Media Length (min to max)	0.25 to 32 inches (6.35 to 812.8 mm)
Roll Size (max), Core Size	Inside diameter 5 inches (125 mm) External diameter 8 inches (200mm) Core size 1 inch (25mm)
Case	Hi-Open™ industrial ABS case with safe close
Mechanism	Hi-Lift™ metal mechanism with wide opening head
Control panel	4 buttons, 16x2 LCD with 2-colour backlight and sophisticated menu configuration system
Flash (Non-Volatile Memory)	8 MB total, 1 MB available for user
Drivers and software	Free-of-charge on CD with printer, including support for various platforms

Size (W x D x H) and Weight	206 x 149 x 150mm, 2.68 Kg (excluding roll holder)
Emulations (Languages)	Citizen Original Commands Datamax® I-Class™ & DMX400™ Cross-Emulation™ - automatic switching between Zebra® ZPL-II® and Datamax® I-Class®, DMX400 Zebra® ZPL-II® BASIC interpreter for data stream processing EPL-2®
RAM (standard Memory)	16 MB total, 1 MB available for user
Media type	Roll or fanfold media; die-cut, continuous or perforated labels, tags, tickets. Inside or outside wound
Cutter	Guillotine type, Dealer Installable
Number of Cuts	300,000 cuts on media 0.06-0.15mm; 100,000 cuts 0.15-0.25mm
Resolution	203 dpi
Main Interface	Dual Interface Serial (RS-232C), USB (version 2.0, full speed)
Interface	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps Ethernet (10/100 BaseT) Parallel (IEEE 1284 compliant)