

Printing Technology	Direct Thermal
Print Speed (maximum)	250 mm/sec.
Print Width (maximum)	72 mm
Media Width (min to max)	59 to 80 mm (+/- 0,5 mm)
Media Thickness (min to max)	53 to 85 µm
Media Sensor	Paper end
Roll Size (max), Core Size	83 mm outside diameter
Case	Stylish flat-top case and top loading
Control panel	2 buttons, 2 LEDs
Flash (Non-Volatile Memory)	8MB
Drivers and software	Free-of-charge from website, including support for various platforms
Size (W x D x H) and Weight	125 x 170 x 108 mm. 1.26 Kg
Warranty	2 years including head and cutter
Emulations (Languages)	ESC/POS™

Barcodes	Code3of9 UPC-A UPC-E EAN-13 (JAN-13) EAN-8(JAN-8), Codabar, ITF CODE39 CODE93 CODE128 CODABAR(NW-7) PDF 417 QR Code GS1-Databar Composit Symb
Media type	Thermal receipt paper
Cutter	Guillotine type, full and partial
Drawer kick-out	CDK / DK connector, RJ12, 2 drawer control
Power supply	100 – 240V, 50-60 Hz, external power supply (supplied) or 24V DC
Reliability	200 Million pulses or 150 Km, 2 million cuts

EMC and safety standards	CE TUV UL C-UL FCC VCCI
Code pages	15 codepages, 17 country tables
Resolution	203 dpi
Main Interface	Dual interfaces: USB + LAN or USB + Serial
Storage environment	-20 to +60°C (10% to 90% RH non condensing)
