

SKU: C11CF40401

[CLOSE ALL](#)

## Technology

<b>Printing Method</b>	Impact dot matrix
<b>Number of Pins</b>	24 pins
<b>Number of columns</b>	136 columns
<b>Pins</b>	24 Needles

---

## Print

<b>Printing Speed</b>	Ultra Speed-Draft: 10 cpi: 550 chars/s, HighSpeed-Draft: 10 cpi: 487 chars/s, 12 cpi: 584 chars/s, Draft: 10 cpi: 366 chars/s, LQ: 10 cpi: 121 chars/s
<b>Barcodes</b>	Code 128, Code 39, EAN-13, EAN-8, Interleaved 2 of 5, POSTNET, UPC-A, UPC-E
<b>Carbon Copies</b>	6 plus one original

---

## Connectivity

<b>Interfaces</b>	Hi-Speed USB - compatible with USB 2.0 specification, Parallel
-------------------	--

---

## Paper / Media Handling

<b>Document Feed</b>	Single sheet front and rear, Continuous media front and rear, Paper output rear
<b>Paper Formats</b>	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Envelopes, Cardboard
<b>Paper Thickness Continuous Paper</b>	0.12 mm - 0.46 mm
<b>Paper Thickness Label Base Sheet</b>	0.16 mm - 0.19 mm
<b>Paper Thickness Multi Part</b>	0.12 mm - 0.46 mm
<b>Paper Thickness Single Sheet</b>	0.065 mm - 0.14 mm

---

## General

<b>Power consumption</b>	49 Watt
<b>Product dimensions</b>	612 x 375 x 177 mm (Width x Depth x Height)
<b>Product weight</b>	9.4 kg
<b>Supported Temperature</b>	Operation 5° C - 35° C
<b>Supported Humidity</b>	Operation 10% - 80%
<b>Compatible Operating Systems</b>	Windows 10, Windows 7, Windows 7 x64, Windows 8, Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2003 x64, Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista, Windows Vista x64, Windows XP, Windows XP Professional x64 Edition SP2 or later

<b>Mean Time Between Failures</b>	25,000 hours
<b>Print Head Life</b>	400 Million Strokes/Wire
<b>Noise</b>	Operation: 55 dB (A)
<b>Noise Level</b>	Operation: 55 dB (A)
<b>What's in the box</b>	Driver and utilities (CD), Power cable, Ribbon, User manual

---

## Other Features

<b>Input Data Buffer</b>	128 kB
--------------------------	--------

---