

SKU: C11CF40402A0

[CLOSE ALL](#)

Technology

Printing Method	Impact dot matrix
Number of Pins	24 pins
Number of columns	136 columns
Pins	24 Needles

Print

Printing Speed	Ultra Speed-Draft: 10 cpi: 550 chars/s
Barcodes	Code 128, Code 39, EAN-13, EAN-8, Interleaved 2 of 5, POSTNET, UPC-A, UPC-E
Carbon Copies	6 plus one original

Connectivity

Interfaces	Hi-Speed USB - compatible with USB 2.0 specification, Parallel, Wired Network
-------------------	---

Paper / Media Handling

Document Feed	Single sheet front and rear, Continuous media front and rear, Paper output rear
Paper Formats	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Envelopes, Cardboard
Paper Thickness Continuous Paper	0.12 mm - 0.46 mm
Paper Thickness Label Base Sheet	0.16 mm - 0.19 mm
Paper Thickness Multi Part	0.12 mm - 0.46 mm
Paper Thickness Single Sheet	0.065 mm - 0.14 mm

General

Power consumption	49 Watt
Product dimensions	612 x 375 x 177 mm (Width x Depth x Height)
Product weight	9.4 kg
Supported Temperature	Operation 5° C - 35° C
Supported Humidity	Operation 10% - 80%
Compatible Operating Systems	Windows 10, Windows 7, Windows 7 x64, Windows 8, Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2003 x64, Windows Server 2016, Windows Vista, Windows Vista x64, Windows XP, XP Professional x64 Edition

Mean Time Between Failures	25,000 hours
Print Head Life	400 Million Strokes/Wire
Noise	Operation: 55 dB (A)
Noise Level	Operation: 55 dB (A)
What's in the box	Driver and utilities (CD), Power cable, Ribbon, User manual

Other Features

Input Data Buffer	128 kB
--------------------------	--------
