

Product Highlights	Compact A3 scanner with a straight-through paper path to feed thick or exceptionally long documents
Throughput Speeds *	70 ppm / 140 ipm
Feeder Capacity	Up to 250 sheets of 80 g/m ² (20 lb.) paper
Connectivity	<ul style="list-style-type: none"> o USB 2.0 o USB 3.2 Gen 1x1 Compatible
Maximum Document Size	305 mm x 4.06 m (12 in. x 160 in.)
Minimum Document Size	63.5 mm x 63.5 mm (2.5 in. x 2.5 in.)
Paper Thickness & Weight	34-413 g/m ² (9-110 lb.) paper
Maximum Optical Capture Resolution	600 dpi
Recommended Daily Volume	Up to 25,000 pages per day
Accessories & Consumables	<ul style="list-style-type: none"> o Black Background o Document Extenders o Feeder Consumables Kits o KODAK A3 Size Flatbed Accessory o KODAK Enhanced Printer Accessory o Printer Ink Cartridge and Carrier
Acoustical Noise	<ul style="list-style-type: none"> o Off or Ready mode: < 30 dB(A) o Scanning: <60 dB(A)
Barcode Reading	<ul style="list-style-type: none"> o Codabar o Code 128 o Code 3 of 9 o EAN-13 o EAN-8 o Interleaved 2 of 5 o PDF417 o QR o UPC-A o UPC-E
Bundled Software	<ul style="list-style-type: none"> o Capture Pro Limited Edition o Smart Touch
Data Security	This scanner processes scanned data exclusively through volatile memory ensuring image data is effectively erased upon shut down. Read more about data security .
Dimensions & Weight	<p>Height: 9.4 in. / 23.8 cm Width: 17 in. / 43.18 cm Depth (with input tray closed): 14.6 in. / 37.1 cm Weight: 35 lbs / 15.8 kg</p>
Electrical Requirements	100-240 V (International); 50-60 Hz
Environmental Certification	<ul style="list-style-type: none"> o 2008 EuP

- o ENERGY STAR Qualified
- o EPEAT Silver

File Format Outputs

- o BMP
- o JPEG
- o Single-page TIFF
- o Microsoft Excel
- o Microsoft Word
- o Multipage TIFF
- o PDF
- o Text searchable PDF
- o PNG
- o RTF

Image Output Resolution Options

Up to 1200 dpi

Operating System Compatibility

- o WINDOWS 8 (32-bit and 64-bit)
- o WINDOWS 7 SP1 (32-bit and 64-bit)
- o WINDOWS 8.1 (32-bit and 64-bit)
- o WINDOWS 10 (32- and 64-bit)
- o WINDOWS Server 2008 R2 X64 Editions
- o WINDOWS Server 2012 R2 X64 Editions
- o WINDOWS Server 2016 X64 Editions
- o WINDOWS VISTA SP2 (32-bit and 64-bit)
- o WINDOWS XP SP3 (32-bit and 64-bit)
- o Ubuntu 16.04 64-bit and 32-bit
- o Ubuntu 18.04 64-bit
- o Open SUSE 11.3 (i586) 32-bit
- o Open SUSE LEAP 15.1 64-bit
- o SUSE Linux Enterprise Desktop 12.2 64-bit
- o SUSE Linux Enterprise Desktop 15 SP1 for 64-bit
- o NeoKylin-Linux-Desktop-6.0 i586 32-bit
- o NeoKylin-Linux-Desktop-6.0-x86_64-B045-20141201 64-bit
- o NeoKylin-Live-Desktop-6.0-x86_64-B060-20160822
- o Neokylin-NKLD-V7_U2-ZX64-REL-build54

Operator Control Panel

Graphical LCD Display with 4 buttons

Operating Temperature / Operating Humidity

- o Operating Temperature 15-35° C (59-95° F)
- o Operating Humidity 15% - 80% RH

Optional Software

- o Capture Pro Software
- o Info Input Solution

Paper Path Options

Documents can exit into the front output tray, or at the rear of the scanner if the straight-through paper path option is manually selected

Paper Handling (SurePath) Features

- o Intelligent Document Protection
- o Length Multifeed Detection
- o Ultrasonic Multifeed Technology

Perfect Page Image Enhancement Software

- o Adaptive threshold processing
- o Aggressive cropping
- o Auto white balance
- o Autocrop
- o Automatic Brightness/Contrast
- o Automatic color balance
- o Automatic color detection
- o Automatic orientation
- o Automatic photo cropping
- o Background color smoothing
- o Barcode reading

- o Black and white image segmentation
- o Brightness and contrast adjustment
- o Color-on-the-fly toggle patch
- o Content-based blank page removal
- o Continuous Scanning Mode
- o Deskew
- o Dual stream scanning
- o Electronic color dropout
- o Enhanced color adjustment
- o Enhanced color management
- o Fixed cropping
- o Fixed thresholding
- o Halftone removal
- o Image edge fill
- o Image hole fill
- o Image merge
- o Interactive color, brightness and contrast adjustment
- o iThresholding
- o Lone Pixel Noise Removal
- o Multicolor dropout
- o Automatic orientation
- o Orthogonal rotation
- o Output Compression-CCITT Group IV, JPEG, Uncompressed Output
- o Rear side printer
- o Relative cropping
- o Image hole fill
- o Sharpening
- o Streak filtering

Power Consumption

- o Running: less than 49 watts
- o Sleep Mode: less than 2.8 watts
- o Standby: less than 0.5 watts

Recommended PC Configuration

INTEL CORE i7 processor @ 3.4 GHz or higher, 4 GB RAM or more (WINDOWS and LINUX)

Scanning Technology

Dual White LED Illumination CCD; Grayscale output bit depth is 256 levels (8-bit); color output bit depth is 24 bits (8 x 3); color capture bit depth is 48 bits (16 x 3)

Standard Software And Drivers

- o KOFAX certified
- o ISIS Drivers
- o LINUX (TWAIN and SANE) Drivers
- o TWAIN Drivers
- o WIA Drivers

Approvals and Product Certifications

- o Argentina (S mark)
- o Australia/New Zealand (RCM)
- o Canada (cTUVus & ICES-003)
- o China (CCC)
- o European Union (CE)
- o European Union (GS Mark)
- o India (BIS)
- o Japan (VCCI)
- o Mexico (NOM)
- o Russia/Eurasian Economic Union (EAC)
- o South Korea (KC)
- o Taiwan (BSMI)
- o US (cTUVus & FCC)