

# Specs

## Printing

<u>Print technology</u>	Direct thermal / Thermal transfer
<u>Colour</u>	
<u>Maximum resolution</u>	203 x 203 DPI
<u>Print speed</u>	152 mm/sec

## Paper handling

Ribbon length	74 m
<u>Maximum roll diameter</u>	12.7 cm
Media thickness	0.08 - 0.19 mm
Media thickness (imperial)	0.003 - 0.0075"
Supported paper width	104 mm
Supported paper width (imperial)	4.09"
Maximum media length	99.1 cm
Maximum media length (imperial)	39"

## Ports & interfaces

<u>Connectivity technology</u>	Wired
<u>RS-232 ports</u>	1
RS-232 interface	
<u>USB 1.1 ports quantity</u>	1
<u>Standard interfaces</u>	Ethernet

## Performance

<u>Internal memory</u>	8 MB
Flash memory	4 MB
Built-in barcodes	CODABAR (NW-7),EAN13,EAN8,Industrial 2/5,Interleaved 2/5,UPC-A,UPC-E

Certification	FCC 15, VCCI, C-Tick, EN55022 B, EN6100-3-2, EN6100-3-3, EN55024, CCCCB IEC 60950: 1991 +A1 +A2 + A3 +A4, TUV NRTL, IRAM, NOM, AAMI
---------------	---

## Design

<u>Product colour</u>	Grey
-----------------------	------

## Power

Power requirements	100 - 240 VAC, 50 - 60 Hz
--------------------	---------------------------

## Operational conditions

Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	40 - 105 °F
<u>Operating temperature (T-T)</u>	5 - 41 °C
Storage temperature (T-T)	-40 - 140 °F

## Weight & dimensions

<u>Width</u>	193 mm
<u>Depth</u>	254 mm
<u>Height</u>	191 mm
<u>Weight</u>	2.1 kg