

ADDITIONAL INFORMATION

Memory

Internal memory	128 MB
Flash memory	256 MB

Printing

Maximum print size	72 x 813 mm
Maximum resolution	203 x 203 DPI
Print technology	Direct thermal
Standard printer languages	CPCL-native, EPL, ZPL
Maximum print height	81.3 cm
Maximum printing width	7.2 cm

Technical details

Certification	FCC Part 15, Subpart B, EN55022 Class-B, EN60950, EN55024, VCCI class B, EN55024, EN61000-4-2, EN61000-4-3, EN61000-4-4, and EN61000-4-5
Colour of product	Black
Dustproof	Yes
International Protection (IP) code	IP43

Certificates

Safety	CE, UL, TUV, CSA
--------	------------------

Data transmission

Bluetooth version	3.0
Bluetooth	Yes

Display

Display resolution	240 x 128 pixels
Display type	LCD

Performance

Built-in barcodes	1D, 2D
-------------------	--------

Design

Type	simple
------	--------

Weight & dimensions

Weight	730 g
Height	84 mm
Width	117 mm
Depth	173 mm

Power

Battery technology	Lithium-Ion (Li-Ion)
Power supply type	AC
Rechargeable	Yes
Power source type	AC, Battery

Operational conditions

Operating relative humidity (H-H)	10 - 90%
Storage temperature (T-T)	-25 - 65 °C
Operating temperature (T-T)	-20 - 50 °C
Storage relative humidity (H-H)	10 - 90%

Ports & interfaces

Serial ports quantity	1
Connectivity technology	Wired & Wireless
USB connector type	Mini-USB B
USB 2.0 ports quantity	1

Paper handling

Media thickness	2.3 - 6.5
Supported paper width	25 - 79
Maximum media length	81.3 cm

Processor

Built-in processor	Yes
--------------------	-----

Mobile operating systems supported

Android, BlackBerry OS, iOS, Windows Mobile

System requirements

Windows operating systems supported

Windows 8