

ADDITIONAL INFORMATION

Memory

Internal memory	8 MB
Flash memory	4 MB

Printing

Maximum resolution	300 x 300 DPI
Print technology	Thermal transfer

Technical details

Certification	FCC 15, VCCI, C-Tick, EN55022 B, EN6100-3-2, EN6100-3-3, EN55024, CCC, CB IEC 60950: 1991 +A1 +A2 + A3 +A4, TUV NRTL, IRAM, NOM, AAMI
Colour of product	Grey

Packaging data

Package weight	4.1 kg
Package type	Box

Paper handling

Media thickness	0.08 - 0.2
Supported paper width	104
Maximum media length	99.1 cm
Maximum roll diameter	127

Design

Type	simple
------	--------

Weight & dimensions

Weight	3.84
Height	191 mm
Width	194 mm
Depth	254 mm

Operational conditions

Operating relative humidity (H-H)	10 - 90%
Storage temperature (T-T)	-40 - 60 °C
Operating temperature (T-T)	5 - 41 °C
Storage relative humidity (H-H)	5 - 95%

Ports & interfaces

Optional connectivity	Bluetooth, Parallel, Wireless LAN
Connectivity technology	Wired
RS-232 ports	1
Standard interfaces	Ethernet

Performance

Built-in barcodes	1D, 2D, CODABAR (NW-7), EAN128, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, Matrix 2/5, PDF417, POSTNET, UPC-A, UPC-E
-------------------	---