

Specs

Printing

<u>Print technology</u>	Thermal transfer
<u>Colour</u>	
<u>Print speed</u>	152 mm/sec
<u>Maximum printing width</u>	10.4 cm

Paper handling

<u>Maximum label width</u>	11.8 cm
<u>Maximum label length</u>	0.991 m
<u>Maximum roll diameter</u>	12.7 cm
<u>Media thickness</u>	0.1905 mm

Ports & interfaces

Ethernet LAN

Wi-Fi

Bluetooth

USB port

USB 2.0 ports quantity 2

Performance

Page description languages EPL2,XML,ZPL II

Internal memory 256 MB

Flash memory 512 MB

Built-in barcodes 1D, 2D, AZTECCODE, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, Data Matrix, EAN13, EAN8, MaxiCode, PDF417, QR Code, UPC-A, UPC-E

Built-in RFID module

Certification IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus

CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, SABS, IN-Metro, BIS, NOM

Design

<u>Product colour</u>	Black
<u>Housing material</u>	Plastic

Power

<u>AC input voltage</u>	100 - 240 V
AC input frequency	50 - 60 Hz
AC adapter output voltage	24 V
AC adapter output current	3.125 A

System requirements

<u>Windows operating systems supported</u>	
<u>Mac operating systems supported</u>	
<u>Mobile operating systems supported</u>	Android, iOS

Operational conditions

Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 95%
<u>Operating temperature (T-T)</u>	4.4 - 41 °C
<u>Storage temperature (T-T)</u>	-40 - 60 °C

Weight & dimensions

<u>Width</u>	202 mm
<u>Depth</u>	254 mm
<u>Height</u>	177 mm
<u>Weight</u>	2.3 kg

Technical details

Sustainability certificates	ENERGY STAR
-----------------------------	-------------

Other features

LED indicators

Clock function