

ADDITIONAL INFORMATION

Memory

Internal memory	256 MB
Flash memory	512 MB

Printing

Print technology	Thermal transfer
Standard printer languages	EPL2, XML, ZPL II
Maximum printing width	10.4 cm

Technical details

Certification	IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus, CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, SABS, IN-Metro, BIS, NOM
LED indicators	1
Colour of product	White
Clock function	Yes

Certificates

Energy Star certified	Yes
-----------------------	-----

Power

Input voltage	90 - 265
Input frequency	50/60

Data transmission

Bluetooth	Yes
-----------	-----

Performance

Built-in barcodes	1D, 2D, AZTECCODE, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, Data Matrix, EAN13, EAN8, MaxiCode, PDF417, QR Code, UPC-A, UPC-E
Mobile operating systems supported	Android, iOS

Design

Type	simple
Housing material	Plastic

Weight & dimensions

Weight	2.3 kg
Height	177 mm
Width	202 mm
Depth	254 mm

Operational conditions

Operating relative humidity (H-H)	10 - 90%
Storage temperature (T-T)	-40 - 60 °C
Operating temperature (T-T)	4.4 - 41 °C
Storage relative humidity (H-H)	5 - 95%

Networking

Ethernet LAN	Yes
--------------	-----

Paper handling

Media thickness	0.08 - 0.305
Maximum label width	11.8 cm
Maximum label length	991 m
Maximum roll diameter	127

Ports & interfaces

USB 2.0 ports quantity	2 inches
------------------------	----------