

ADDITIONAL INFORMATION

Memory

Internal memory	128 MB
Flash memory	128 MB

Printing

Maximum resolution	203 x 203 DPI
Print technology	Thermal transfer
Maximum printing width	10.4 cm

Weight & dimensions

Weight	11.36
Height	277 mm
Width	242 mm
Depth	432 mm

Operational conditions

Operating relative humidity (H-H)	20 - 85%
Storage temperature (T-T)	-40 - 60 °C
Operating temperature (T-T)	0 - 40 °C
Storage relative humidity (H-H)	5 - 85%

Ports & interfaces

Optional connectivity	Ethernet, Parallel
Connectivity technology	Wired & Wireless
USB 2.0 ports quantity	1
RS-232 ports	1

Performance

Built-in barcodes	1D, 2D, Code 128 (A/B/C), Code 39, Code 93, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, MaxiCode, PDF417, POSTNET, TLC39, UPC-A, UPC-E
Ribbon length	450 m
Ribbon width	11 cm

Design

Type	simple
------	--------

Display

Display	LCD
---------	-----

Technical details

Certification	IEC 60950, EN 55022 B, EN 55024, EN 61000-3-2, EN 61000-3-3, cTUVus, CE, FCC-B, ICES-003, VCCI, C-Tick, NOM, S Mark, CCC, GOST-R, KCC, BSMI
Colour of product	Black, White

Certificates

Energy Star certified	Yes
-----------------------	-----

Paper handling

Media thickness	0.076 - 0.025
Maximum label width	11.4 cm
Maximum label length	0.991 m
Maximum media length	3.99 m