

Specifications

Product Highlights	The best Interactive Multifeed Recovery system of any scanner on the market today. Monitor multifeeds and quickly choose to accept, ignore or rescan images before sending to an application.
Throughput Speeds *	110 ppm / 220 ipm
Feeder Capacity	Up to 500 sheets of 80 g/m ² (20 lb.) paper
Connectivity	USB 3.2 Gen 1x1 Certified
Maximum Document Size	305 mm x 9100 mm (360 in. x 12 in.)
Paper Thickness & Weight	45-200 g/m ² (12-110 lb.) paper
Maximum Optical Capture Resolution	600 dpi
Accessories & Consumables	<ul style="list-style-type: none">o Document Extenderso Feeder Consumables Kitso Imaging Guide Seto KODAK A3 Size Flatbed Accessoryo KODAK Enhanced Printer Accessoryo Printer Cleaning Padso Printer Ink Cartridge and Carriero Switchable Black/White Background
Acoustical Noise	Scanning: <63 dB(A)
Approvals and Product Certifications	<ul style="list-style-type: none">o Argentina (S mark)o Australia/New Zealand (RCM)o Canada (cTUVus & ICES-003)o China (CCC)o European Union (CE)o European Union (GS Mark)o India (BIS)o Japan (VCCI)o Mexico (NOM)o Russia/Eurasian Economic Union (EAC)o South Korea (KC)o Taiwan (BSMI)o US (cTUVus & FCC)
Barcode Reading	<ul style="list-style-type: none">o Codabaro Code 128o Code 3 of 9o EAN-13

- EAN-8
- Interleaved 2 of 5
- PDF417
- QR
- UPC-A
- UPC-E

Data Security

This scanner processes scanned data exclusively through volatile memory ensuring image data is effectively erased upon shut down. Read more about [data security](#).

Dimensions & Weight

Height: 34.79 cm (13.7 in.)
Width: 48.9 cm (19.2 in.)
Depth: 46.73 cm (18.4 in.) with tray closed
Depth: 61.30 cm (24.1 in.) with tray open
Weight: 30.4 kg (67 lb.)

Electrical Requirements

100-240 V (International); 50-60 Hz

Environmental Certification

- 2008 EuP
- ENERGY STAR Qualified
- EPEAT Silver

File Format Outputs

- BMP
- JPEG
- Single-page TIFF
- Microsoft Excel
- Microsoft Word
- Multipage TIFF
- PDF
- Text searchable PDF
- PNG
- RTF

Image Output Resolution Options

Up to 600 dpi

Minimum Document Size

50.8 mm x 63.5 mm (2 in. x 2.5 in.)

Operating System Compatibility

- WINDOWS 8 (32-bit and 64-bit)
- WINDOWS 8.1 (32-bit and 64-bit)
- WINDOWS 10 (32- and 64-bit)
- WINDOWS 11 (64 bit)
- WINDOWS Server 2012 R2 X64 Editions
- WINDOWS Server 2016 X64 Editions
- WINDOWS Server 2019 X64 Editions
- WINDOWS Server 2022 X64 Editions
- Ubuntu 20.04 64-bit
- Ubuntu 18.04 64-bit
- Open SUSE 13.2 (i586) 32-bit
- Open SUSE LEAP 15.2 64-bit
- SUSE Linux Enterprise Desktop 12.2 64-bit

- SUSE Linux Enterprise Desktop 15 SP1 for 64-bit
- Neokylin-NKLD-V7_U2-ZX64-REL-build54

Operating Temperature / Operating Humidity

- Operating Temperature 15-35° C (59-95° F)
- Operating Humidity 15% - 80% RH

Operator Control Panel

3.5 inch (89 mm) graphical color LCD with operator control buttons

Optional Software

- Capture Pro Software
- Info Input Solution

Paper Path Options

Documents can exit into the front output tray, or at the rear of the scanner if the straight-through paper path option is manually selected

Paper Handling (SurePath) Features

- Controlled stacking
- Enhanced jam recovery
- Intelligent Document Protection
- Interactive multifeed with image display on host
- Interactive Operator Control Panel (OCP)
- Metal (staple) detection
- Ultrasonic Multifeed Technology
- Operator overrides
- Length Multifeed Detection

Perfect Page Image Enhancement Software

- Adaptive threshold processing
- Aggressive cropping
- Auto white balance
- Autocrop
- Automatic color balance
- Automatic color detection
- Automatic orientation
- Barcode reading
- Color-on-the-fly toggle patch
- Content-based blank page removal
- Deskew
- Electronic color dropout
- Enhanced color adjustment
- Enhanced color management
- Fixed cropping
- Fixed thresholding
- Front side printer
- Halftone removal
- Image edge fill
- Image hole fill
- Image merge
- iThresholding
- Lone Pixel Noise Removal
- Multicolor dropout
- Automatic orientation
- Orthogonal rotation
- Output Compression-CITT Group IV, JPEG

- Output Compression-COM1 Group IV, or EC, Uncompressed Output
- Relative cropping
- Image hole fill
- Sharpening
- Streak filtering

Power Consumption

- Running: less than 130 watts
- Sleep Mode: less than 1.5 watts
- Standby: less than 0.5 watts

Price

\$\$\$

Recommended Daily Volume

Up to 65,000 pages per day

Recommended PC Configuration

INTEL CORE i5 (Sandy Bridge or newer), running @ 2.7 GHz or higher, USB port 3.0 (Super Speed) or 2.0 (High Speed), 4 GB RAM or more

Scanning Technology

Dual White LED Illumination CCD; Grayscale output bit depth is 256 levels (8-bit); color output bit depth is 24 bits (8 x 3); color capture bit depth is 48 bits (16 x 3)

Standard Software And Drivers

- KOFAX certified
 - ISIS Drivers
 - LINUX (TWAIN and SANE) Drivers
 - TWAIN Drivers
 - WIA Drivers
-