General

Bundled Software	ScanFront Administration Tool
Dimensions (W x D x H)	Feed tray and eject tray closed: 305 × 281.9 × 230.1 mm Feed tray and eject tray open: 305 × 628.5 × 366.1 mm
Ejection pockets	-
Interface	Hi-Speed USB 2.0 (Type A x 3), LAN 10Base-T/100Base-TX/1000Base-T connector
MICR	-
On-Board Jogger	-
Operating Environment	Temperature: 10 - 32.5°C Humidity: 20 - 80% RH
Supported Operating System	Linux
Options/ Consumables	Exchange Roller Kit, Flatbed Scanner Unit 102, Carrier Sheet (Passport), Carrier Sheet (A4)
Power	AC 100-240 V
Power Consumption	Scanning: 36 W, Sleep mode: 2.0 W, Power Turned OFF: 0.2 W
Power Consumption Weight	
	Power Turned OFF: 0.2 W
Weight	Power Turned OFF: 0.2 W
Weight Scanning Document	Power Turned OFF: 0.2 W Approx. 4.5 kg Automatic
Weight Scanning Document Feeding Method	Power Turned OFF: 0.2 W Approx. 4.5 kg Automatic Page Separation mode: Weight: 27 to 209 g/m² Thickness: 0.04 – 0.25 mm Non Separation mode: Weight: 27 to 255 g/m²
Weight Scanning Document Feeding Method Document thickness - Plain Paper	Power Turned OFF: 0.2 W Approx. 4.5 kg Automatic Page Separation mode: Weight: 27 to 209 g/m² Thickness: 0.04 – 0.25 mm Non Separation mode: Weight: 27 to 255 g/m²
Weight Scanning Document Feeding Method Document thickness - Plain Paper Document thickness - Postcard Document thickness - Business	Power Turned OFF: 0.2 W Approx. 4.5 kg Automatic Page Separation mode: Weight: 27 to 209 g/m² Thickness: 0.04 – 0.25 mm Non Separation mode: Weight: 27 to 255 g/m² Thickness: 0.04 – 0.30 mm -
Weight Scanning Document Feeding Method Document thickness - Plain Paper Document thickness - Postcard Document thickness - Business Card Document thickness - Card	Power Turned OFF: 0.2 W Approx. 4.5 kg Automatic Page Separation mode: Weight: 27 to 209 g/m² Thickness: 0.04 – 0.25 mm Non Separation mode: Weight: 27 to 255 g/m² Thickness: 0.04 – 0.30 mm - 380 g/m² or less

A4/LTR

uggested Daily Volume (Scans)	6,000
	A4 / LTR, Portrait, 200dpi: Black and White: 45ppm (simplex) / 90ipm (duplex) Grayscale: 45ppm (simplex) / 90ipm (duplex) Colour: 45ppm (simplex) / 90ipm (duplex)
canning Side	Simplex / Duplex
	Black and white, Error diffusion, Advanced Text Enhancement II, 256 level grayscale, 24-bit color, Auto Color Detection
	Pass-through desktop scanner with network compatibility
	CIS
	100 x 100dpi / 150 x 150dpi / 200 x 200dpi / 240 x 240dpi / 300 x 300dp / 400 x 400dpi / 600 x 600dpi
aximum Resolution	600 dpi
ght source	LED (red, green and blue)
can	
ocument size - Magnetic card	-
ocument size - Plastic card	-
	88 x 125 mm (ISO standard) When scanning, be sure to open the passport and insert it in the provided carrier sheet (for passports) beforehand.
ocument size - Card (ISO/IEC ompliant)	54 × 86 mm
ocument size - Business card	50 × 85 mm
ocument size - Postcard	-
ocument size - Long Document ode	Up to 3,048 mm in 200 dpi
<u>.</u>	Width: 50 – 216 mm, Length: 54 – 356 mm