

Tech Specs

The product features and specifications are subject to change without prior notice

Technology

Scanner Type

Flatbed Scanner, Sheetfed Scanner

Optical Resolution

1,200 DPI x 1,200 DPI (Horizontal x Vertical)

ADF Minimum Document Size

100 mm x 148 mm (Horizontal x Vertical)

ADF Maximum Document Size

215.9 mm x 1,016 mm (Horizontal x Vertical)

Paper Formats

A4 (21.0x29.7 cm), A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B5, Letter, Legal, Executive

Scanning color depth

Input: 48 Bits Color / 16 Bits Monochrome , Output: 24 Bits Color / 8 Bits Monochrome

Ultrasonic Sensor

Yes

Category

Small & Compact, High Capacity, General Office

Scanner

Light Source

ReadyScan LED technology

LCD Display

Optional Network Interface Panel

Scan speed

Scanning Speed

Monochrome: 25 pages/min - Color: 25 pages/min , Resolution: 200 / 300 dpi, Monochrome: 50 image/min - Color: 50 image/min , Resolution: 200 / 300 dpi

Paper / Media Handling

Paper Setting Capacity

100 Sheets

Paper weight

Auto loading: 50 - 128 g/m²

Reliability Daily Duty Cycle

3,000 pages

Automatic Document Feed

100 pages

Duplex Scan

Yes

Scanning Features

Features

Skip blank page, Pre-defined scanning settings, Automatic de-skew, Automatic multi-document recognition, Automatic B/W colour original detection, Dual Image Output (Windows only), Auto-rotation, Text enhancement, Edge fill, Unsharp Mask (USM), Book spine correction, Automatic Folder Creation, Barcode Recognition, Zonal OCR A & B support, Manual / Automatic Job Separation

Output formats

JPEG, TIFF, multi-TIFF, PDF, PDF / batch, searchable PDF, secure PDF, PDF/A

File compression features

Hardware JPEG compression, TIFF Compression (JPEG(7) , CITT G4, LZW), PDF Compression

Advanced document integration

Scan to Email, Scan to FTP, Scan to Microsoft SharePoint®, Scan to Print, Scan to Web folders, Scan to Network folders

Connectivity

Interfaces

USB 2.0, Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T) (optional)

Network Interface Panel / Unit

Optional

Ethernet settings

10BASE-T / 100BASE-TX / 1000BASE-T / Full-duplex / Half-duplex

Panel type

5-line LCD with Push Scan features

Push scan features

Yes (with Document Capture Pro solutions)

General

Supply Voltage

AC 100 V - 240 V, 50 Hz - 60 Hz

Product dimensions

495 x 360 x 217 mm (Width x Depth x Height)

Product weight

9.8 kg

Drivers

TWAIN, WIA, ISIS (Web download)

Included Software

Epson Document Capture Pro (Windows only), Epson Document Capture Pro Server (on free download), Epson Event Manager (Mac Only), Epson Scan

Compatible Operating Systems

Citrix XenApp 5.0, Citrix XenApp 6.0, Mac OS 10.4.11 or later (Epson Scan Only), Presentation Server 4.5, Terminal Service, Windows 7, Windows 7 x64, Windows 8, Windows 8.1, Windows Server 2003 (32/64bit), Windows Server 2008 (32/64bit), Windows Server 2008 R2, Windows Vista, Windows Vista x64, Windows XP, Windows XP x64, Windows Server 2003 R2

Power consumption

44.5 Watt, 12 Watt (economy), 1.6 Watt (standby)

Supported Humidity

Operation 10% - 80%, Storage 10% - 85%

Supported Temperature

Operation 5° C - 35° C, Storage -25° C - 60° C

What's in the box

AC adapter, Main unit, Setup guide, Software (CD), USB cable, User manual (CD), Warranty document

Options

Roller Assembly Kit

Other

Warranty

12 months On-site service
