

# Specifications in detail

## Technology

### Printer Type

12 Colour 44"/1118mm

### Print Technology

Canon Bubblejet on Demand 12 colours integrated type (12 chips per print head x 1 print head)

### Print Resolution

2,400 x 1200 dpi

### Number of Nozzles

18,432 nozzles (1536 nozzles x 12 colour)

### Line Accuracy

±0.1% or less

User adjustments necessary. Printing environment and media must match those used for the adjustments.

CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only

### Nozzle Pitch

600 dpi x 2 includes Non-firing nozzle detection and compensation system

### Ink Droplet Size

minimum 4 pl per colour

### Ink Capacity

Sales Ink: 160ml/330ml/700ml

Bundled Starter Ink: 330ml

### Ink Type

Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow, Photo Cyan, Photo Magenta, Gray, Photo Gray, Red, Blue, Chroma Optimiser

### OS Compatibility

Microsoft Windows: 32 Bit, Vista, 7,8, 8.1,10

Server 2008, 64 Bit: Vista, 7,8, 8.1,10,

Server 2008/R2, Server 2012/R2, Windows Server 2019

Apple Macintosh: OS X 10.11.6、 macOS 10.12 ~ macOS 10.15

### Printer Languages

SG Raster (Swift Graphic Raster), PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)

### Standard Interfaces

USB A Port: USB Memory Direct Print for JPEG/PDF files

USB B Port: Built-in Hi-Speed USB 2.0

Ethernet: 10/100/1000 base-T

Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b

\*Please refer to user manual how to activate/deactivate the wireless LAN

## Memory

### Standard Memory

3 GB

### Hard Drive

500GB (Encrypted HDD)

## Printing Speed

### Media Type (A0 page size)

Print Mode: Print Time

Plain Paper (A0 page size)

Fast: 01.37 min

Standard: 02.49 min

Coated Paper (A0 page size)

Standard: 02.49 min

High Quality: 05:35 min

Glossy Photo Paper (A0 page size)

Standard: 05.35 min

High Quality: 08:50 min

\*Output Image: ISO JIS SCID N5

## Media Handling

### Media Feed and Output

Upper Roll Paper: One Roll, Front-loading, Front Output

Lower Roll Paper: One Roll, Front-loading, Front Output

Cut Sheet: Front-loading, Front Output (Manual feed using media locking lever)

### Media Width

Roll paper: 152.4 – 1118 mm

Cut sheet: 152.4 – 1118 mm

### Media Thickness

Roll/Cut: 0.07 - 0.8 mm

### Minimum Printable Length

203.2 mm

### Maximum Printable Length

Roll paper: 18 m (Varies according to the OS and application)

Cut sheet: 2133.6mm

### Maximum Media Roll Diameter

170 mm

### Media Core Size

Internal diameter of roll core: 2 2/3"

### Margins Recommended area

Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm

Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

### Margins Printable area

Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm

Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm

Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm

### Media Feed Capacity

Roll Paper: Two rolls. Automatic switching is possible.

Cut Sheet: 1 sheet

### Media Take-up roll unit

Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll

### Borderless Printing Width (Roll Only)

515mm(JIS B2), 728mm(JIS B1), 1030mm(JIS B0), 594mm(ISO A1), 841mm(ISO A0), 10", 14", 17", 24", 36", 42", 44", 257mm(JIS B4)\*, 297mm(ISO A3)\*, 329mm(ISO A3+)\*, 420mm(ISO A2)\*, 6", 8"\*, 12", 16"\*, 20", 22", 30"\*, 300mm\*, 500mm, 600mm 800mm, 1000mm and custom roll width (152.4 ~ 1118mm)

\*Some environmental conditions may not produce the desired result

### Maximum number of delivered prints

Standard position: 1 sheet

Flat position: A2 landscape, glossy paper less than 10 sheets, Coated paper less than 20 sheets (excludes strong curled condition)

## Dimensions and Weight

## Physical Dimensions and Weight

---

W x D x H

1593 x 984 x 1168 mm (Basket Open)

1593 x 766 x 1168 mm (Basket Closed)

145 kg (including Roll Holder Set and Roll unit, excluding ink and print heads)

## Packaged Dimensions and Weight

Printer (Main unit with pallet): 1820 x 915 x 1042 mm

177 kg

Roll Unit: 1727 x 562 x 461 mm

33 kg

# Power and Operating Requirements

---

## Power Supply

AC 100-240V (50-60Hz)

## Power Consumption

Operation: 107 W or less

Sleep mode: 2.0W or less

Default setting for the time to enter the Sleep mode: Approx. 5 Minutes

Power off: 0.3 W or less

## Operating Environment

Temperature: 15~30°C, Humidity: 10~80% RH (no dew condensation)

## Acoustic Noise (Power/Pressure)

Operation: approx. 48 dB (A) (Glossy paper, Print priority: Standard)

Standby: 35 dB (A) or less

Operation: 6.6 Bels or less (Glossy paper, Image, Print priority: Standard) (Measured on ISO 7779 standard)

## Regulations

Europe: CE mark, Russia: EAC

## Certificates

TUV, CB

# What's Included

---

## What's in the Box?

Printer, 1 print head, 3 inch paper core attachment, Power cable, 1 set of starter ink tanks, Set up guide, Safety/Standard Environment leaflet, User software CD-ROM (Win), Poster Artist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet

## Software Included

imagePROGRAF PRO Printer Driver, and PosterArtist Lite

Other software available as Download from Web.

# Options

---

## Optional Items

2/3" Roll Holder: RH2-46

Roll Unit: RU-43

# Consumables

---

## User Replaceable Items

Ink Tank: PFI-1100 (160ml), PFI-1300 (330ml), PFI-1700 (700ml)

Print Head: PF-10

Cutter Blade: CT-07

Maintenance Cartridge: MC-30

