



KONICA MINOLTA

bizhub PRO 951

✎ Entry-level production, high-level dependability



Giving Shape to Ideas

bizhub PRO 951 

B/W PRODUCTION PRINTING SYSTEM

Technical specifications

PRINTER SPECIFICATIONS

Print speed A4	Up to 95 ppm
Print speed A3	Up to 55 ppm
Print resolution	1,200 x 1,200 dpi
Gradations	Up to 256 levels

SYSTEM SPECIFICATIONS

Paper weight	Standard: 40–300 gsm; optional (with PF-706): 40–350 gsm; in duplex mode: 50–300 gsm
Duplex unit	Non-stacking type
Paper sizes	A5 to SRA3 Standard: min.: 182 x 139 mm; max.: 324 x 463 mm; optional: min.: 95 x 139 mm*; max.: 324 x 483 mm**
Maximum image area	314 x 478 mm
Maximum paper input capacity	Max.: 9,000 sheets; main unit: up to 3,000 sheets; LU-409: up to 4,500 sheets; LU-410: up to 4,000 sheets; PF-706: up to 6,000 sheets
Maximum paper output capacity	Up to 4,200 sheets
Warm-up time	Less than 390 sec.
Main unit dimensions (W x D x H)	990 x 910 x 1,454 mm
Main unit weight	Approx. 372 kg

CONTROLLER SPECIFICATIONS

Hardware	Embedded controller
CPU	Pentium M 2.0 GHz
RAM	2 GB
HDD	250 GB or above
Page description languages	PCL 5e/XL (PCL 6); Adobe PS 3; TIFF; PDF

SCANNER SPECIFICATIONS

Scan Speed A4	Up to 95 opm
Scan Speed A3	Up to 55 opm
Scan resolution	1,200 dpi; 600 dpi; 400 dpi; 300 dpi; 200 dpi
Scan modes	TWAIN scan; Scan-to-HDD; Scan-to-FTP; Scan-to-SMB; Scan-to-email
Scan formats	PDF; TIFF; secured PDF; XPS

- All specifications refer to A4-size paper of 80 gsm quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5 % coverage of A4).
The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any prices or specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

COPIER SPECIFICATIONS

Copy speed A4	Up to 95 cpm
Copy speed A3	Up to 55 cpm
Copy resolution	600 x 600 dpi
Gradations	256 gradations
FCOT	Less than 3.4 sec. (A4 LEF)
Magnification	25 – 400 % in 0.1 % steps
Multiple copies	1 – 9,999

ACCESSORIES

Automatic document feeder	Max.: 100 sheets
Large capacity tray	Large capacity paper feeding unit LU-409 Paper capacity: up to 4,500 sheets; paper weight: 40–300 gsm; standard paper sizes: A4; min. paper size: 250 x 176 mm; max. paper size: 314 x 229 mm
Large capacity tray	Large capacity paper feeding unit LU-410 Paper capacity: up to 4,000 sheets; paper weight: 40–300 gsm; standard paper sizes: SRA3; min. paper size: 195 x 203 mm; max. paper size: 324 x 483 mm
Paper feed unit	Paper feed unit PF-706 3 magazines; paper capacity: up to 6,000 sheets; paper weight: 40 – 350 gsm; standard paper sizes: A5 to A3+ (SRA3); min. paper size: 95 x 139 mm; max. paper size: 324 x 463 mm
Staple finisher	Stapling unit FS-532 Stapling of up to 100 sheets; 2-point and corner stapling; variable staple length (cutting mechanism); output for up to 4,200 sheets (A4); sub tray for up to 200 sheets; auto-shift sorting and grouping
Booklet finisher	Saddle stitching kit SD-510 (for FS-532) Booklet making of up to 20 sheets (80 images); saddle stitching; cover sheets from 50 to 300 gsm; output tray for booklets; multi-letter fold-in (up to 5 sheets); multi-half fold (up to 5 sheets)
Z-fold and punch finisher	Z-fold unit ZU-608 2 and 4 hole punching, Z-folding and half folding
Punch kit	Punch kit PK-505 (for FS-532) Punching (2 and 4 holes selectable)
Post inserter	Post insertion unit PI-502 (for FS-532) Insertion of preprinted sheets; PI trays for 200 sheets each
Multi punching unit	Multi (GBC) punching unit GP-501 Multi punching of A4 sheets; user replaceable die sets for: velo bind, plastic comb, wire bind, colour coil, pro click; paper weight: 75 – 216 gsm
Auto ring binder	Auto ring binder GP-502 Stacking, punching and binding of books, up to 102 sheets; self-adjusting bind elements (one size fits all); paper weight: content 75–120 gsm; cover 163–216 gsm

Your Konica Minolta Business Solutions Partner:

Simitri HD
High Definition Polymerised Toner

Simitri
with Biomass

