



## KV-S1026C DOCUMENT SCANNER

### Fast & compact for improved efficiency.

The Panasonic KV-S1026C scanner features a slim and compact body, ideal for business use where space is limited, and offers easy operation with advanced features.

- Fast - High-Speed Scanning at 30 pages per minute

Routine scanning is quick and easy. Scan through mountains of documents and large amounts of daily forms, quickly and effortlessly converting them into digital data.

- Easy to use

Simply press the button and send documents to three pre-registered destinations such as a folder, an email address or a printer.

- Equipped with unique high end features

Features the 'Double Feed Skip' button which enables the scanning of documents such as envelopes and pages with sticky notes. KV-S1026C is able to scan very thin paper from 20g/m<sup>2</sup> and long paper.

---

#### Features

- High-speed scanning up to 30ppm / 60ipm
- 50 Sheet Automatic Document Feeder
- Slim, compact body (W 303 mm x D 177 mm x H 137 mm )
- 3 customisable Single Touch Scan Keys

- Active Double Feed Prevention Roller System
- Simple Touch Free Scanning
- Embossed Card Scanning
- Includes Panasonic Image Capture Plus Software

# KV-S1026C PRODUCT GUIDE AND SPECIFICATIONS

## Quick

### High-Speed Scanning

Routine scanning is quick and easy. Scan through mountains of documents and large amounts of daily forms, quickly and effortlessly converting them into digital data.



## Easy

### Single Touch Scan

Simply press the button and send documents to three pre-registered destinations.



## Reliable

### Active Double Feed Prevention

The rotating double feed roller ensures the preceding documents are kept in the feeding area while the top page is fed into the scanner, thus preventing double feeding.



Flatbed Scanner  
KV-SS081

Model		KV-S1026C
SCANNER TYPE	Duplex Sheet Feed Scanning	
SCANNER TECHNOLOGY	1-Line CIS (Contact Image Sensor)	
SCANNING SPEED*1 (A4, Portrait)	Up to 30 ppm / 60 ipm (Binary 200 dpi) Up to 20 ppm / 40 ipm (Colour 200 dpi)	
RESOLUTION (Colour and B/W)	Resolution : 100 - 600dpi (1dpi step) Optical : 300/600dpi	
AUTOMATIC DETECTION	Ultrasonic Double Feed Detection	
IMAGE COMPRESSION	JPEG (Grayscale/Colour)	
IMAGE OUTPUT	Binary, Grayscale, Colour, MultiStream (Colour & Binary or Gray & Binary)	
BINARY MODE HALFTONE	Dither, Error Diffusion	
IMAGE CONTROL	Automatic Binary/Color Distinction, Multi Color Drop Out, Blank Page Removal, Double Exposure, Smooth Background, Automatic Cropping, De-skewing, Dynamic Threshold, White Level From Paper, Image Emphasis (5 steps), Gamma Correction, Automatic Separation, Noise Reduction, Shadow Removal, Mirror Image, Monochrome Reversing, 2-Page Separation and much more.	
OTHER FUNCTIONS	Zone OCR (a function of the Image Capture Plus software that adds characters from the document to the output file name), Separation sheet, Single Touch Scan, Skip key	
DOCUMENT	SIZE (ADF)	Minimum 48 mm x 70 mm (1.9 in. x 2.8 in.) length Maximum 216 mm x 2,540 mm (8.5 in. x 100 in.) length
	WEIGHT/THICKNESS*2	Single 20 - 209 g/m2 (5.4 lbs. - 55 lbs.) Continuous 20 - 209 g/m2 (5.4 lbs. - 55 lbs.)
AUTOMATIC DOCUMENT FEEDER	Up to 50 sheets (20 lbs., 80 g/m2), 3 hard cards (ISO 7810 ID-1)	
SUPPORTED OPERATING SYSTEM	Windows® XP SP3 or later (32-bit), Windows Vista® SP2 or later (32/64-bit), Windows® 7 and Windows® 8 (32/64-bit)	
INTERFACE	High-Speed USB 2.0, Up to 480 Mbps transfer rate	
POWER REQUIREMENT	AC 100 - 120 V 50/60 Hz, AC 200 - 240 V 50/60 Hz	
POWER CONSUMPTION	Scanning mode 17 W or less Idle mode 4.5 W or less Sleep mode 1.6 W or less Power off mode 0.3 W or less	
OPERATING ENVIRONMENT	Temperature 10 °C - 35 °C (50 °F - 95 °F) Humidity 20 % RH - 80 % RH	
STORAGE ENVIRONMENT	Temperature 0 °C - 40 °C (32 °F - 104 °F) Humidity 10 % RH - 80 % RH	
EXTERNAL DIMENSIONS*3 (W x D x H)	303 mm x 177 mm x 137 mm (11.9 in. x 7 in. x 5.4 in.) without Feed tray	
WEIGHT*3	2.7 kg (5.9 lbs.)	
ACCESSORIES	DVD-ROM : Drivers and Utilities for Windows / Manuals Driver software ISIS / TWAIN Application software Image Capture Plus Safety Guide, Quick Reference Guide, Mixed batch card guide, AC adapter & Power cord, USB cable	
OPTIONS	ROLLER EXCHANGE KIT	KV-SS058 (Double-feed prevention roller x 1, Paper feed roller x 1)
	ROLLER CLEANING PAPER	KV-SS03
	FLATBED SCANNER	KV-SS081

\*1 The scanning speed differs depending on the host computer, the operating system, the application, the measuring method, the quantity of data in the image, and the paper type. The scanning speed depends on a measuring method of Panasonic.

\*2 "Weight in pounds" of paper represents the weight of 500 (432 x 559 mm / 17 x 22 inches) sheets.

\*3 Dimensions and weight are approximate

#### Trademarks and registered trademarks

- ENERGY STAR and the ENERGY STAR mark are registered U.S. marks.
- ISIS® is a registered trademark or trademark of EMC Corporation in the United States and other countries.
- Microsoft®, Windows® and Windows Vista® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
- All other brand or product names are the property of their respective holders.
- Design and specifications are subject to change without notice.

This Product is designed to reduce hazardous chemical substances along with the RoHS directive.

**Panasonic**  
ideas for life