KYOCERA
KYOCERA Document Solutions Europe

> Home   > Products   ⌄ ECOSYS P6021cdn Home and Office Colour A4 Printer - Technical Specs

ECOSYS P6021cdn Home and Office Colour A4 Printer

| Product Overview | Product Gallery | Options & Consumables | Technical Specs |

General

General type	Colour Printer for A4 format
Technology	KYOCERA ECOSYS, Colour Laser
Engine speed	Up to 21 pages per minute in A4 in colour and b/w
Resolution	600 x 600 dpi, MultiBit-Technology for print quality of up to 9,600 x 600 dpi
Warm-up time	Approx. 32 seconds or less from power on
Time to first print	Approx. 10.5 seconds or less in b/w, Approx. 12 seconds or less in colour
Dimensions (W x D x H)	390 x 523 x 370 mm
Weight	Approx. 29.3 kg
Power consumption	Printing: 353 W, Ready mode: 61 W, Low-Power Mode: 24W, Sleep-mode: 4 W
Power source	220 ~ 240 V, 50/60 Hz
Noise (ISO 7779 / ISO 9296)	Noise (Sound pressure level: ISO 7779 / ISO 9296) Printing in colour: 48.2 dB(A) LpA Ready mode: Immeasurably low
Safety standards	GS, TÜV, CE - This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.
General memory	512 MB RAM, max. 1,536 MB

Paper Handling

Input capacity	Max. 50-sheet multi-purpose tray, 60–220 g/m², A4, A5, A6, B5, B6, letter, legal, custom (70 x 148 to 216 x 356 mm); max. 250-sheet universal paper cassette, 60–163 g/m², A4, A5, A6, B5, letter, legal, folio, custom (105 x 148 to 216 x 356 mm)
Max. input capacity with options	1,300 sheets
Duplex unit	Double-side printing as standard; 60–163 g/m²; A4, A5, B5, Letter, Legal
Output capacity	250-sheet face-down
Further information	All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Print

Processor	PowerPC 465S / 667 MHz
Controller language	PRESCRIBE IIc
Emulations	PCL 6 (5c, XL), KPDL 3 (PostScript* 3 compatible), XPS Direct Print, PDF Direct Print 1.7, with automatic emulation sensing
Fonts	93 scalable fonts for PCL/PostScript, 8 fonts for Windows Vista, 1 bitmap font, 45 barcodes (e.g. EAN8, EAN13, EAN128) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)

Integrated Accounting	100 department codes
Features	AirPrint, IPP printing, Email printing, Secure printing via SSL, IPSec, HTTPS, SNMPv3, IPPS, POP over SSL, SMTP over SSL, Private Print, Toner save mode
Applicable OS (Print)	All current Windows operating systems, Mac OS X Version 10.4 or higher, UNIX, LINUX as well as other operating systems on request

Interfaces

Standard interface	USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT) Slot for optional internal print server or SSD hard disc Slot for optional SD/SDHC-Card

WARRANTY

Warranty	1-year warranty as standard (depending on the country). KYOCERA guarantees the drums and developers for 3 years or maximum 100,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.

RELATED DOWNLOADS

- ❯ ECOSYS P6021cdn Documentation
- ❯ ECOSYS P6021cdn Utility
- ❯ ECOSYS P6021cdn Driver

❯ Sitemap   ❯ Legal Notices and Terms   ❯ Access to Information Manual

© KYOCERA Document Solutions Europe B.V.