Flatbed Scanner Unit 101.

Optional Flatbed Scanner.

you can

Simple to connect, the optional Flatbed Scanner Unit 101 sets a new standard of productivity.

The ultimate workgroup convenience.
Here's the ideal way to scan bound, fragile or outsize documents. Plug-and-go simplicity plus easy operation make it the perfect flatbed scanner to share in and across departments – and it's easy to store when not in use.

Drive up productivity.
You can speed up processing with continuous 'open scanning' thanks to the unique ambient light cancelling mode; and with scanning speeds of under three seconds to scan an A4 page, the Flatbed Scanner Unit 101 helps teams work up to 50% more productively than many competitors' products.

High performance as standard.
The Flatbed Scanner Unit 101 has a high optical resolution of 1200dpi and provides access to a host of advanced image processing features. So you're assured premium quality results scan after scan.

Outstanding features and benefits include:

- Simple USB connection to a wide range of DR-series scanners
- High-speed capture gives up to 50% greater productivity
- A unique ambient light cancelling mode for rapid open scanning
- Capture documents as large as Legal size
- A flexible cover takes the strain out of scanning bulky volumes
- High-quality 1200dpi scanning
- A seamless interface with imageFORMULA devices for dual capture
- Access to the DR-series' powerful image processing features
- Easily stowed away when not in use
- Compliance with ENERGY STAR standards for lower running cost

imageFORMULA

Canon

Specifications: Flatbed Scanner Unit 101

Type	Desktop A4 Flatbed Scanner Option
Document Reading Sensor	CCD Sensor
Optical Resolution	1200dpi
Light Source	LED (RGB)
Reading Side	Front
Interface	High speed USB 2.0 (Type A x 1, Type B x 1)
Dimensions	290 (W) x 513 (D) x 88.5 (H)mm
Weight	3.5Kg (Without AC Adaptor)
Power Requirements	AC100 – 240V (50/60Hz)
Power Consumption	Scanning: 15.2W, Sleep Mode: 5.1W, Power Turned Off, Less than 0.5W
Operating Environment	10 - 32.5ºC (50 - 90.5ºF), Humidity: 20 - 80% RH
Environmental Compliance	RoHS and ENERGY STAR

READING SPEED (A4, Portrait)	Flatbed Scanner Unit 101	
B & W / Greyscale Colour	200 / 300dpi 200dpi 300dpi	3 seconds 3 seconds 4 seconds

DOCUMENT SPECIFICATIONS	
Width	Up to 215.9mm (up to Legal)
Length	Up to 355.6mm (up to Legal)

OUTPUT	
Mode	Black and White, Error Diffusion, Advanced Text Enhancement (II), 256-level Greyscale (8-bit), 24-bit Colour, Auto Colour Detection
Resolution	100 x 100dpi, 150 x 150dpi, 200 x 200dpi, 240 x 240dpi 300 x 300dpi, 400 x 400dpi, 600 x 600dpi, 1200 x 1200dpi

PRODUCT FEATURES	
	Size Detection Area, Ambient Light Cancelling Mode (Inherits image processing function from connected DR-series scanners)

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ™ and ®: All company and / or product names are trademarks and / or registered trademarks of their respective manufacturers in their markets and / or countries.

Compatible DR-Series Scanners

	DR-2010C DR-2510C	DR-3010C	DR-4010C DR-6010C	DR-6050C DR-7550C DR-9050C
Document Size	A4	A4	A4	A3
Feeder Type	ADF	ADF	ADF	ADF
Reading Speed (A4, 200dpi, Portrait) **B & W / Greyscale**	20ppm / 40ipm 25ppm / 50ipm	30ppm / 60ipm	42ppm / 84ipm 60ppm / 120ipm	60ppm / 120ipm 75ppm / 150ipm 90ppm / 180ipm
Colour	20ppm / 40ipm 25ppm / 50ipm	30ppm / 60ipm	42ppm / 84ipm 60ppm / 120ipm	60ppm / 120ipm 75ppm / 150ipm 90ppm / 180ipm
Feeder Capacity (80g/m²)	50 sheets	50 sheets	100 sheets	300 sheets 500 sheets 500 sheets
Suggested Daily Duty Cycle (Scans/day)	1,500	3,000	5,000 7,500	12,000 15,000 18,000
Bundled Software	CaptureOnTouch, CapturePerfect, PaperPort, BizCard, Omnipage, Adobe Std, Kofax VRS (2510C only)	CapturePerfect, PaperPort, BizCard, Omnipage, Adobe Std, Kofax VRS	CapturePerfect, Adobe Std, Kofax VRS	CapturePerfect, Kofax VRS

Connectivity Diagram

DR-2010C / DR-2510C / DR-3010C

When using the DR scanner that uses an AC adapter, Flatbed Scanner Unit 101 is connected between DR scanner and PC.

DR-4010C / DR-6010C / DR-6050C / DR-7550C / DR-9050C

When using with the DR scanner that has power supply built in, connect both Flatbed Scanner Unit 101 and DR scanner directly to the PC.