

# bizhub 283

# **✓** Functionality



- Black & white



– Black & white – PCL/PS Local/network



- Colour - Black & white TWAIN Network Scan-to-SMB

- Scan-to-Box - Scan-to-USB

- Scan-to-eMail - Scan-to-Home - Scan-to-FTP - Scan-to-Me - Scan-to-WebDAV - Scan-to-DPWS





PC-FaxSuper G3 Fax

- Distribution - Sharing Box-to-Box - Reprint


- Box-to-USB



# Technology



# Option diagram



# Finishing options













mixmedia







Corner stapling

Two-point stapling

Two-hole punching

Four-hole punching

# Descriptions

bizhub 283	Black & white communication center with 28 ppm.
	Standard Emperon <sup>™</sup> print controller with PCL 6,
	PostScript 3, PDF 1.7 and XPS support. Paper capacity
	of 500 + 500 sheets and 150-sheet manual bypass.
	Media from A6 to A3 and 60-210 gsm. 2 GB memory,
	and Gigabit Ethernet.
DF-621 Document	Automatic document feeding of up to 100 originals
feeder	and the second s
OC-509 Original cover	Cover instead of ADF
PC-109 1 x Universal	A5-A3; 1 x 500 sheets; 60-90 gsm
tray	
PC-208 2 x Universal	A5-A3; 2 x 500 sheets; 60-90 gsm
tray	
PC-409 Large capacity	A4; 2,500 sheets; 60-90 gsm
tray	
DK-508 Copier desk	Storage of paper; etc.
FS-527 Staple finisher	50 sheet stapling, output capacity 3,200 sheets
PK-517 Punch kit	Either 2 hole or 4 hole punching (permanent adjustment)
SD-509 Saddle kit	Booklet finishing
JS-603 Job separator	Separation of e.g. fax and copy/print output

FS-529 Staple finisher	50 sheet stapling, output capacity 300 sheets
JS-505 Job separator	Separation of e.g. fax and copy/print output
WT-506 Working table	Authentication device placement
FK-508 Fax board	Super G3 fax
MK-726 Fax mount kit	I/F board for fax FK-508
HD-516 Hard disc	250 GB; required for i-Option, box, authentication,
	animation guidance, mobile printing, etc.
KH-101 Keyboard holder	To place the USB keyboard
EK-604 USB I/F kit	USB keyboard connection
EK-605 USB I/F kit	USB keyboard connection and Bluetooth
ID-Card reader	Various card technologies
AU-102 Biometric	Finger vein scanner
authentication	
SC-507 Security Kit	Copy Guard function
LK-101v2 i-Option	Web browser, image panel
licence	
LK-102 i-Option licence	PDF enhancement
LK-105 i-Option licence	Searchable PDF
UK-203 i-Ontion memory	Memory extension for i-Ontion

# **✓** Technical specifications

#### COPIER SPECIFICATIONS

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD polymerised toner
Copy/print speed A4	Up to 28 cpm
Copy/print speed A3	Up to 16 cpm
Autoduplex speed A4	Up to 28 cpm
1st copy/print time	4.2 sec.
Warm-up time	Approx. 25 sec. <sup>1</sup> (without HDD)
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Original format	A5-A3
Magnification	25-400 % in 0.1% steps; auto-zooming
Copy functions	Chapter; cover and page insertion; proof copy (print and
	screen); adjustment test print, digital art functions,
	job setting memory; poster mode; image repeat; overlay;
	stamping; copy protection

### PRINTER SPECIFICATIONS

Print resolution	Equivalent to 1,800 x 600 dpi
Controller CPU	MPC8533E @ 667 MHz
Page description	PCL 6c (PCL 5c + XL3.0)
language	PostScript 3 (CPSI 3017)
	XPS
Operating systems	Windows 2000
	Windows XP (32/64)
	Windows VISTA (32/64)
	Windows 7 (32/64)
	Windows Server 2000
	Windows Server 2003/2008 (32/64), 2008 R2 (64)
	Macintosh OS X 10.x
	Unix, Linux, Citrix
Printer fonts	80 PCL Latin
	137 PostScript 3 Emulation Latin
Print functions	Direct print of PCL, PS, TIFF, XPS, PDF and encrypted PDF
	files; mixmedia and mixplex; "Easy Set" job programming;
	overlay (HDD required); watermark; copy protection, secure
	print (HDD required), USB direct print

### SCANNER SPECIFICATIONS

Scan speed	Up to 70/70 opm (300 dpi via opt. ADF)
(mono/colour)	Up to 42/42 opm (600 dpi via opt. ADF)
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Network TWAIN scan
	Scan-to-eMail (Scan-to-Me)
	Scan-to-FTP
	Scan-to-SMB (Scan-to-Home)
	Scan-to-Box (HDD required)
	Scan-to-WebDAV
	Scan-to-DPWS
	Scan-to-USB
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; Outline PDF;
	Searchable PDF (optional); XPS; Compact XPS
Scan destinations	2,100 (single + group); LDAP support
Scan functions	Annotation (text/time/date) for PDF (HDD required);
	up to 400 job programs

### FAX SPECIFICATIONS

Fax standard	Super G3 (optional)
Fax transmission	Analogue
	i-Fax (HDD required)
	IP-Fax (HDD required)
Fax resolution	Max.: 600 x 600 dpi (ultra-fine)
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,100 (single + group)
Fax functions	Polling; time shift; PC-Fax; receipt to confidential box;
	receipt to email/FTP/SMB; up to 400 job programs

 $<sup>^{\</sup>mbox{\scriptsize 1}}$  Warm up time may vary depending on the operating environment and usage

#### USER BOX SPECIFICATION (HDD REQUIRED)

Max. user boxes	1,000
Max. storable	Up to 3,000 documents or 10,000 pages
documents	
Type of user boxes	Public
	Personal (with password or authentication)
	Group (with authentication)
Type of system boxes	Secure print
	Encrypted PDF print
	Fax receipt
	Fax polling
User box functionality	Reprint
	Combination
	Download
	Sending (email/FTP/SMB and Fax)
	Copy box to box

#### SYSTEM SPECIFICATIONS

System memory	2,048 MB
System hard disc	250 GB (optional)
HDD required for	Complete box functionality (incl. secure printing),
	Animated guidance, i-Option, PSES, mobile printing, OpenAP
	Copy functions: Program job, overlay
	Print functions: Secure print
	Scan functions: Scan annotation
	Fax functions: i-Fax, IP-Fax
	Authentication functions: PageScope Authentication Manager
	USB direct print: Encrypted PDF
Interface	10-Base-T/100-Base-T/1,000-Base-T Ethernet; USB 2.0
Network protocols	TCP/IP (IPv4 / IPv6); IPX/SPX; NetBEUI; AppleTalk (EtherTalk);
	SMB; LPD; IPP; SNMP; HTTP
Frame types	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP
Automatic document	Up to 100 originals; A6-A3; 35-210 gsm simplex;
feeder (optional)	50–128 gsm duplex
Printable paper size	A6-A3; customised paper sizes
	(90-297 x 139.7-431.8 mm)
Printable paper weight	60–210 gsm
Paper input capacity	Standard: 1,150 sheets
	Max.: 3,650 sheets
Tray 1	500 sheets; A5-A3, 60-90 gsm
Tray 2	500 sheets; A5-A3, 60-90 gsm
Tray 3 (optional)	500 sheets; A5-A3, 60-90 gsm
Tray 3 + 4 (optional)	2 x 500 sheets; A5-A3, 60-90 gsm
Large capacity tray	2,500 sheets; A4, 60–90 gsm
(optional)	
Automatic duplexing	A5–A3; 60–90 gsm
Finishing modes	Offset; group; sort; staple; punch; centre-fold; booklet
(optional)	
Output capacity	Max.: 3,200 sheets
(with finisher)	
Output capacity	Max.: 250 sheets
(without finisher)	
Stapling	50 sheets or 48 sheets + 2 cover sheets (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Booklet	15 sheets or 14 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	75 sheets (tray)
Copy/print volume	Rec.: 4,800 prints; Max.: 28,000 prints
(monthly)	

Toner lifetime	17,500 pages
Drum/developer	100,000 pages
lifetime	
Power consumption	220-240 V / 50/60 Hz
	Less than 1.5 KW
System dimensions	623 x 794 x 700
(W x D x H, mm)	
System weight	Approx. 66 kg

SYSTEM FEATURES	
Security	ISO 15408 EAL3; IP filtering and port blocking;
	SSL2; SSL3 and TSL1.0 network communication;
	IPsec support; IEEE 802.1x support; user authentication;
	Authentication log; secure print (HDD required);
	Hard disc overwrite (8 standard types);
	Hard disc data encryption (AES 128);
	Memory data auto deletion; confidential fax receiving;
	Print user data encryption; copy protection
	(Copy Guard and Password Copy optional)
Accounting	Up to 1,000 user accounts; Active Directory support
	(user name + password + email + SMB folder)
	User function access definition
	Biometric authentication (finger vein) optional
	ID-Card authentication (ID-Card reader) optional
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility
	Log Management Utility

- All specifications refer to A4-size paper of 80 gsm quality.
   The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
   The stated life expectancy of each consumable is based on specific operating conditions such as
- page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.

  Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any prices or specifications mentioned will be error-free.
   All brand and product names may be registered trademarks or trademarks of their respective
- holders and are hereby acknowledged.




















SAP® Printer Vendor Solution







