WorkForce M105

DATASHEET / BROCHURE









Epson's first monochrome integrated ink tank system printer, with Wi-Fi connectivity, for ultra-low-cost office printing

The Epson WorkForce M105 is an single-function monochrome integrated ink tank system printer with Wi-Fi connectivity. This continuous ink system is ideal for home office and small office users, who are looking to cut their printing costs, and comes with two Epson genuine ink bottles – one starter bottle and one standard 140ml bottle. Standard ink bottles offer a page yield of 6,000 pages¹.

Epson's fast-drying genuine pigment ink ensures business documents are water, smudge and fade resistant, while Micro Piezo technology offers Epson-quality document printing. In addition, a 12-month (or 50,000-page) warranty, and additional service support, provide peace of mind and help if you need it.

The purpose-built ink tank system is fully integrated into the printer, so you can enjoy reliable printing without the mess or hassle often associated with nongenuine refills and third-party ink tank systems. The Epson genuine ink bottles make it easy to refill the ink tank with their clear labelling and drip-free nozzle.

The Epson WorkForce M105 is network-ready for sharing across small workgroups, but can also be used on individual user desktops thanks to its compact size. Fast print speeds of up to 15ppm² also help boost office productivity, so you don't have to wait around for prints. In addition, you can produce a variety of additional materials, such as headed paper, business cards and envelopes.

The Epson WorkForce M105 has a small footprint that easily complements any work environment it is in. And thanks to its quick start-up and low energy usage, this ENERGY STAR-qualified printer is ideal for any energy-efficient office.

KEY FEATURES

- Ultra-low-cost printing

 Monochrome integrated ink tank system
- Wi-Fi printer
 Print wirelessly
- Epson-quality prints
 Micro Piezo technology
- Peace of mind
 Epson service warranty





PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method On-demand inkjet (Piezo electric)

Minimum Droplet Size 3 pl, With Variable-Sized Droplet Technology

Nozzle Configuration 360 Nozzles black
Application Home, Office Desktop

PRINT

Printing Speed ISO/IEC 24734 15 pages/min Monochrome

Maximum Printing Speed 34 pages/min Monochrome (plain paper)

Printing Resolution 1,440 x 720 dpi
Max Duty cycle 5,000 pages per month

The maximum number of printed pages per month based on the performance capabilities of

the printer, including ISO rated print speeds and paper handling capabilities.

Colours Black, Black

For detailed information on printing speeds please visit http://www.epson.eu/testing.

PAPER / MEDIA HANDLING

Paper Formats A4, A5, A6, B5, C6 (Envelope), DL (Envelope), No. 10 (Envelope), Letter, 10 x 15 cm, 13 x 18

cm, 13 x 20 cm, 20 x 25 cm, 100 x 148 mm, 16:9, Legal

Paper Tray Capacity 100 Sheets Standard, 100 Sheets maximum

Number of paper trays

CONNECTIVITY

Interfaces Hi-Speed USB - compatible with USB 2.0 specification, Wireless LAN IEEE 802.11b/g/n

WLAN Security WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA PSK (AES)

GENERAL

Energy Use 2 W (sleep mode), 13 W (printing), ENERGY STAR® qualified

Product dimensions 435 x 267 x 148 mm (Width x Depth x Height)

Product weight 3.4 kg

Noise Level 5.2 B (A) according to ISO 7779 pattern with Epson Premium Glossy Photo Paper / Photo RPM

mode - 38 dB (A) according to ISO 9296

Compatible Operating Mac OS 10.5.8 or later, Windows 7, Windows 7 x64, Windows 8 (32/64 bit), Windows Vista,

Systems Windows Vista x64, Windows XP, Windows XP x64

LOGISTICS INFORMATION

SKU	C11CC85301 C11CC85301DA
EAN code	8715946524177
Dimensions Single Carton	1100 x 3165 x 1030 mm
Carton Weight	153 Kg
Multiple Order Quantity	1 Units
Country of Origin	Indonesia
Pallet Size Euro	36 Units

WorkForce M105

WHAT'S IN THE BOX

- 1 x 140ml individual starter black ink bottle plus 1 x 140ml T7741 black ink bottle
- Driver and utilities (CD)
- Power cable
- Setup guide
- User manual (CD)

INK CARTRIDGE COMPATIBILITY



774



INK YIELD DATA



774 black ink bottle 774

•	6,000 pages*
Included bottle yield - black (2 bottles)	11,000 pages*

* Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 19752. 11,000 pages yield based on two ink bottles included with this printer. 6,000 pages yield based on T7741 ink bottle sold separately. Quoted yields are NOT based on ISO/IEC24711. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature.















* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00 Poland 0-0-800 4911299 (0,16 zl/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711)

465-9621 Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal – 0,99 kr/min, Lokala samtal – 0,30 kr/min, Utlandssamtal – 0,89 kr/min)

Switzerland 022 592 7923 Turkey (0212) 3360303 United Kingdom 0871 222 6702

- 1. Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 19752. Quoted yields are NOT based on ISO/IEC 24711. Quoted yield may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature
- 2. The average of ESAT from the Office Category Test for B&W simplex, determined in accordance with ISO/IEC24734

