

---

# Epson FX-890A

---

DATASHEET

---



The fast and reliable Epson FX-890A is the ideal dot matrix printer for producing mission-critical documents, such as passenger manifests.

Developed specifically for the demanding airport environment, it has a rugged build with a shock-resistant cover and sheet feeder, plus a heavy-duty, reinforced acrylic tear-off bar that is independent to the cover for durability and ease of replacement.

One of the fastest printers in its class, the FX-890A prints up to 680cps at 12cpi in ultra-high-speed draft mode to help ensure operations run smoothly. Downtime is minimised with a ribbon yield of 7.5 million characters and a mean time between failure of 20,000 hours.

Easy to install, the FX-890A has parallel and USB interfaces, plus a Windows® driver for straightforward integration into any Windows application<sup>5</sup>.

Epson is the world's number one manufacturer of dot matrix printers, with a product range that offers the ultimate in high-speed, low cost, reliable and durable printing across all stationery types.

---

## KEY FEATURES

---

- Reliable, high-speed, 9-pin dot matrix printer designed for airports
- Rugged build with shock-resistant cover and sheet-feeder
- Independent, reinforced acrylic tear-off bar
- Prints up to 680cps at 12cpi in ultra-high-speed draft mode
- Ribbon yield of up to 7.5 million characters
- Mean time between failure of 20,000 hours
- Locked front cover as standard to prevent security issues and damage
- Parallel and USB interfaces
- Windows driver for easy integration into any Windows application
- ENERGY STAR-qualified for reduced impact on the environment and low power consumption

## PRODUCT SPECIFICATIONS

<b>PRINTER TYPE</b>	
Printing method	2 x 9 pins
Number of pins in head	Black
Colour	Bi-direction with logic seeking
Print direction	ESC/P and IBM PPDS emulation
Control code	
<b>PRINT</b>	
Speed	HighSpeed-Draft: 10cpi <sup>1</sup> : 566cps <sup>4</sup> , 12cpi <sup>1</sup> : 680cps <sup>4</sup> , NLQ: 12cpi <sup>1</sup> : 125cps <sup>4</sup> , 10cpi <sup>1</sup> : 104cps <sup>4</sup> , Draft: 10cpi <sup>1</sup> : 419cps <sup>4</sup>
Carbon Copies	6 plus one original
Character tables	PC850, PC708, PC437, ISO-8859-15, PC720, PC858, Roman 8, PC864
<b>PRINTABLE COLUMNS</b>	
Pitch:	10cpi <sup>1</sup> , 80cpi <sup>2</sup> , 12cpi <sup>1</sup> , 96cpi <sup>2</sup> , 15cpi <sup>1</sup> , 120cpi <sup>2</sup> , 17cpi <sup>1</sup> , 137cpi <sup>2</sup> , 20cpi <sup>1</sup> , 160cpi <sup>2</sup>
<b>PAPER/MEDIA HANDLING</b>	
PAPER PATH	Manual Insertion: front or rear in, top out, optional CSF: rear in, top out
Copy	Push tractor: front or rear in, top out, optional pull tractor: front or rear or bottom in, top out
<b>RIBBON</b>	
Colour	Black
Life	Approx. 7.5 million characters (Draft 10cpi <sup>1</sup> , 14 dots/character)
<b>OPERATION</b>	
Operating temperature	5 to 35°C
Operating humidity	10 to 80% RH
Supported OS	Windows XP (32bit) SP2 or later Professional Windows Vista (32bit/64bit) SP1 or later Ultimate/Enterprise/Business Windows 7 (32bit/64bit) Ultimate/Enterprise/Professional Windows Server 2003 (32bit/64bit) SP2 Standard/Enterprise Windows Server 2008 Standard/Enterprise (32bit/64bit), R2 Standard/Enterprise (64bit)
<b>GENERAL</b>	
Mean time before failure	20,000 POH
Print head life	400 million strokes/wire
Power consumption	Approx. 56W (ISO/IEC10561 Letter pattern) Approx. 4.4W (115V Ver) / Approx. 4.8W (230V Ver) in sleep mode <sup>3</sup> Approx. 0W in power off mode
Frequency	50 - 60Hz
Voltage	AC 100 to 240V
Noise level	Approx. 55dB(A) (ISO 7779 pattern)
Input data buffer	128KB
Dimensions (W x D x H)	414 x 350 167mm
Weight	Approx. 7.2kg
<b>WARRANTY</b>	
	1 year – Repair or Replace

## WHAT'S IN THE BOX

- Epson FX-890A printer
- User's manual
- Driver disk
- Ribbon cartridge (black)
- Power supply cable

## OPTIONS

- Warranty extension
- Ribbon cartridge (BLACK)
- High capacity cut sheet feeder (150 sheets)
- Single bin cut sheet feeder (50 sheets)
- Pull tractor unit
- Roll paper holder
- Front sheet guide
- Front paper guide
- Serial I/F card
- Epson Net 10/100 Base TX. INT. Print Server



## LOGISTICS

	Epson FX-890A printer	Epson ribbon cartridge
SKU code		
Minimum order quantity / per carton		
Carton weight		
Carton dimensions (W x D x H)		

\* Worldwide sales volume, IDC  
 1 cpi: characters per 25.4 mm (characters per inch)  
 2 cpl: characters per line  
 3 When the printer is idle for 5 minutes, it automatically enters sleep mode.  
 4 cps: characters per second  
 5 Windows is a registered trademark of Microsoft Corporation in the United States and other countries



For more information please contact:

Telephone: 0871 222 6702 (UK)\*  
 01 436 7742 (Republic of Ireland)  
 E-mail: enquiries@epson.co.uk  
 Chat: etalk.epson-europe.com  
 Fax: 0871 222 6740

Web: www.epson.co.uk  
 www.epson.ie

\* Calls cost 10p per minute plus network extras.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

# EPSON®