

PLQ-30M

DATASHEET



Ideal for financial and government institutions, this quiet, fast and power-efficient passbook printer has a low TCO.

The 'M' version of the PLQ-30 has a MSRW head. Customers and staff alike will appreciate the PLQ-30M's unobtrusive noise levels, which are as low as 55dBA. It's efficient, too – the print speed enhancer enables fast printing of bit image data under Windows environments to help cut queues.

Low total cost of ownership

Delivering substantial cost and energy savings, the PLQ-30M has a very low standby power consumption of 4.5W. Further reducing TCO, it can print around 10 million characters in draft mode between ribbon changes.

Flexible

It offers excellent passbook handling and data processing flexibility, thanks to its 128kb memory and capacity for passbooks up to 2.6mm thick.

Easy installation

Simple to install, the PLQ-30M features a choice of emulations plus parallel, serial and USB interfaces as standard for an easy fit into most IT environments.

Ultra-high-speed draft mode

High speed print speeds of 585 cps.

KEY FEATURES

- **Media flexibility**
Trouble-free handling of cheques and passbooks
- **Quiet operation**
Noise levels as low as 55dBA
- **Energy-efficient**
4.5W standby power consumption
- **Low TCO**
Long-life ribbon
- **Flexible**
Handles passbooks up to 2.6mm thick

PRODUCT SPECIFICATIONS

TECHNOLOGY

Number of Pins	24 pins
Number of columns	94 columns

PRINT

Printing Speed	HighSpeed-Draft: 585 cpi: 10 chars/s, 520 cpi: 10 chars/s, Draft: 390 cpi: 10 chars/s, NLQ: 195 cpi: 10 chars/s, LQ: 130 cpi: 10 chars/s
Barcodes	Coda bar (NW-7), Code 128, Code 39, EAN-13, EAN-8, Industrial 2 of 5, Interleaved 2 of 5, UPC-A, UPC-E
Carbon Copies	6 plus one original
Character Tables	PC437, PC850, PC858, PC864, ISO-8859-1, ISO-8859-15
Printing Resolution	60,120,240 x 60 dpi

CONNECTIVITY

Interfaces	USB 2.0 Type B, Bidirectional parallel, RS-232
------------	--

PAPER / MEDIA HANDLING

Document Feed	Single sheet front, Paper output front and rear, bulk measurement: yes
Paper Formats	Sheet Paper (single- and multi-layer), Envelopes
Paper Thickness Multi Part	0.12 mm - 0.53 mm
Paper Thickness Single Sheet	0.065 mm - 0.19 mm

GENERAL

Energy Use	64 W, 4.5 W (standby)
Supply Voltage	AC 220 V - 240 V, 50 Hz - 60 Hz
Energy Star	No
Product dimensions	384 x 280 x 203 mm (Width x Depth x Height)
Product weight	8.9 kg
Temperature	Operation 5° C - 35° C, Storage -30° C - 60° C
Compatible Operating Systems	Windows 10, Windows 7, Windows 8, Windows Vista, Windows XP
Mean Time Between Failures	12,000 Hours
Print Head Life	400 Million Strokes/Wire
Humidity	Operation 10% - 80%

OTHER FEATURES

Emulations	ESC/P, IBM PPDS, PR2
Input Data Buffer	128 kB

OTHER

Warranty	12 months Carry in Optional warranty extension available
----------	---

LOGISTICS INFORMATION

SKU	C11CB64501
EAN code	8715946605395
Country of Origin	Indonesia
Layer	18 Units
Layer Block	24 Units

PLQ-30M

WHAT'S IN THE BOX

- Power cable
- Ribbon
- Setup guide
- User manual (CD)

SUPPLIES

- Epson SIDM Black Ribbon Cartridge for PLQ-20/22, 3-Pack (C13S015339) (C13S015339)

OPTIONAL ACCESSORIES

- Epson SIDM Space Saving Kit for PLQ-20/22 series C12C802202
- Epson SIDM Paper Roll Holder for LX-300-II/1170II, FX-890/A, FX-2190, LQ-690/300+II series C12C811141



For more information please contact:

Home users: 0343 90 37766
Business users*: 0871 42 37766
Republic of Ireland: 01 436 7742
Or visit us at <https://www.epson.co.uk/contactus>
* 10p per minute plus network extras.

Web: www.epson.co.uk
www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.

EPSON®