

## SF9350

<b>Master Making/Printing Methods</b>		High-speed digital master-making/Fully automatic printing
<b>Original Type</b>		Book or sheet
<b>Master Making Time*<sup>1</sup></b>	Quick Master Making mode	- Approx. 14 seconds (A4, long-edge feed) - Approx. 18 seconds (A4, short-edge feed)
	Normal master making mode	- Approx. 16 seconds (A4, long-edge feed) - Approx. 20 seconds (A4, short-edge feed)
<b>Resolution</b>	Scanning	600 dpi × 600 dpi
	Printing	600 dpi × 600 dpi, Quick Master Making mode: 600 dpi × 400 dpi
<b>Maximum Scanning Area</b>		297 mm × 432 mm
<b>Print Paper Weight</b>		46 gsm to 210 gsm
<b>Print Paper Size*<sup>2</sup></b>		100 mm × 148 mm to 310 mm × 432 mm
<b>Maximum Printing Area</b>		291 mm × 413 mm
<b>Paper Feed Tray Stacking Capacity</b>		1000 sheets* <sup>3</sup> , stacking height of 110 mm or lower
<b>Paper Receiving Tray Stacking Capacity</b>		1000 sheets* <sup>3</sup> , stacking height of 110 mm or lower
<b>Print Speed</b>		6 levels: 60, 80, 100, 120, 130, and 150 ppm* <sup>4</sup>
<b>Print Position Adjustment</b>		Horizontal: ±15 mm, Vertical: ±10 mm
<b>Image Processing Mode</b>		Line, Photo (Standard/Portrait), Duo (Standard/Line/Photo), Pencil (Darker/Lighter)
<b>Print Reproduction Ratio</b>		Zoom (50% to 200%), Free, 100% reduction ratio, Margin+ (90% to 99%), 4 levels of enlargement (163%, 141%, 122%, 116%), 4 levels of reduction (87%, 82%, 71%, 61%)
<b>User Interface</b>		Color touch panel
<b>Functions</b>		Image, Contrast, Size, Paper Size Detection, Dot Process, Contrast Adj., Tone Curve, Multi-up Print, Book Shadow, Top Margin Adj., Binding Margin Adj., Max. Scan, Ink Saving, Quick Master Making, Preview, ADF-Semi-Auto* <sup>5</sup> , Storage, Overlay, Print Speed Adj., Print Density Adj., Print Position Adj., Interval, Renew Page, Auto Page Renewal, Rotate, Special Paper Ctrl, Program, Job Separation* <sup>5</sup> , Job Memory, Reservation, Editor, Idling Action, Confidential, My Direct Access, Meter Display, ID Counter Report, Proof Copy, Direct Printing, USB Job List, Scanning mode, Admin., Auto Sleep, Auto Power-OFF, Power-OFF Schedule, ECO mode, Protect, RISO iQuality System
<b>Ink Supply</b>		Full automatic (1000 ml/cartridge)
<b>Master Supply/Disposal</b>		Full automatic (A3: approx. 220 sheets per roll)/Disposal capacity: approx. 100 sheets
<b>Power Source</b>		AC 100-240 V, 50-60 Hz <3.4-1.6 A>

<b>Power Consumption</b>	Standard	Max.: 300 W, Ready: 20 W or lower, Sleep: 5 W or lower, Power-OFF: 0.5 W or lower
	Optional Accessories Connected <sup>*6</sup>	Max.: 315 W, Ready: 30 W or lower, Sleep: 10 W or lower, Power-OFF: 0.5 W or lower
<b>Dimensions (WxDxH)</b>	In use	1415 mm × 670 mm <sup>*7</sup> × 1065 mm <sup>*8</sup>
	In storage	780 mm × 670 mm <sup>*7</sup> × 1065 mm <sup>*8</sup>
<b>Required Space (WxDxH)</b>		1415 mm × 1240 mm × 1515 mm <sup>*8</sup>
<b>Weight</b>		102 kg <sup>*9</sup>
<b>Safety Information</b>		IEC-60950-1 compliant, indoor, pollution degree 2 <sup>*10</sup> , at altitudes of 2000 m or lower

\*1 Measurement value when set to 100% reproduction ratio.

\*2 When the optional Wide Stacking Tray is installed, you can use paper up to a size of 310 mm × 555 mm by setting [Custom Paper Entry].

\*3 When using the following weight of paper: 64 gsm to 80 gsm

\*4 If the temperature of the inside of the print drum (cylinder) is less than 15°C, [150 ppm] is not usable.

\*5 Optional accessories required.

\*6 When all the following optional accessories are installed, Auto Document Feeder, Job Separator, Key/Card Counter.

\*7 The depth does not include the stabilizers for the stand.

\*8 The height includes the stand.

\*9 The weight does not include the ink, master roll, and stand.

\*10 The pollution degree of the usage environment due to dirt and dust in the air. Degree "2" corresponds to a general indoor environment.

Notes: The specifications are subject to change without prior notice.