

Zebra DS2208 1D/2D LED Black Handheld bar code reader



Manufacturer:	Zebra
Category:	Printers & Scanners
Sub-Category:	Barcode Readers
SKU:	DS2208-SR7U2100SGW
EAN:	5711783381266

Description

AFFORDABILITY AND SIMPLICITY DELIVERED

2D barcodes have made their way to your Point of Sale, appearing on everything from the items your customers are purchasing to printed and electronic coupons and loyalty cards.

Your 1D scanner can't capture the new 2D codes, leading to exceptions that slow down the check-out process and frustrate customers at that key last personal touchpoint in your store.

But with the DS2200 Series, you can scan it all. You get an affordable 1D/2D imager that doesn't compromise performance or features for price. And you can choose the model that best fits your POS needs — the corded DS2208 or the cordless DS2278. The DS2200 Series — the affordability your budget demands, with the deployment, ease of use and management simplicity your business requires.

Specifications

Scanning	
Linear (1D) barcodes supported	Codabar,Code 11,Code 128,Code 39,Code 93,EAN-13,GS1 DataBar Expanded,Interleaved 2 of 5,MSI,U.P.C.
2D (matrix & stacked) barcodes supported	Aztec Code,Composite Codes,Data Matrix,Han Xin,MaxiCode,Micro QR Code,PDF417,QR Code,TLC-39
Motion tolerance (cm/s)	13
Yaw reading angle	-65 - 65°
Working distance	36.8 cm
Wavelength	645 nm
Tilt reading angle	-65 - 65°
Sensor type	LED
Scanner type	1D/2D
Pitch reading angle	-65 - 65°
Optical sensor resolution (W x H)	640 x 480 pixels
Ports & interfaces	
Wireless range	10 m

Connectivity technology	Wired
Bluetooth version	4.0 BLE
Standard interfaces	USB,RS-232,RS-485,Keyboard wedge
Technical details	
Type	Handheld bar code reader
RoHS compliance	Yes
LED indicators	Yes
International Protection (IP) code	IP42
Product colour	Black
Certification	EN 60950-1 2ed + A11 + A1 + A12 + A2:2013, IEC 60950-1 2ed + A1 + A2, UL 60950-1, CAN/CSA-C22.2 No. 60950-1-07 IEC 62471 EN 55022 (Class B); EN 55032 (Class B) EN 55024 EN 61000-3-2 EN 61000-3-3 47 CFR Part 15, Subpart B, Class B ICES-003 Issue 6, Class B
Design	
Type	Handheld bar code reader
RoHS compliance	Yes
LED indicators	Yes
International Protection (IP) code	IP42
Product colour	Black
Certification	EN 60950-1 2ed + A11 + A1 + A12 + A2:2013, IEC 60950-1 2ed + A1 + A2, UL 60950-1, CAN/CSA-C22.2 No. 60950-1-07 IEC 62471 EN 55022 (Class B); EN 55032 (Class B) EN 55024 EN 61000-3-2 EN 61000-3-3 47 CFR Part 15, Subpart B, Class B ICES-003 Issue 6, Class B
Power	
Power consumption	250 mA
Power source type	DC
Battery life	100 h
Battery technology	Lithium-Ion (Li-Ion)
Battery capacity	2400 mAh
AC adapter output voltage	5 V
Operational conditions	
Storage temperature (T-T)	-40 - 70 °C
Operating temperature (T-T)	0 - 50 °C
Operating relative humidity (H-H)	5 - 95%

Weight & dimensions

Width	66 mm
Depth	99 mm
Height	165 mm
Weight	161.6 g

Packaging data

Charging base	No
Cables included	Micro-USB

Packaging content

Charging base	No
Cables included	Micro-USB