

## Specifications

<b>Print quality</b>	
Maximum resolution	203 x 203 DPI
Maximum printing width	10.4 cm
Maximum print height	3.99 m
<b>Printing</b>	
Colour	No
Print speed	356 mm/sec
Maximum resolution	203 x 203 DPI
Maximum printing width	10.4 cm
Maximum print size	104 x 3988 mm
Maximum print height	3.99 m
Print technology	Direct thermal / thermal transfer
<b>Design</b>	
Display	LCD
Product colour	Black,Grey
<b>Display</b>	
Display	LCD
<b>Networking</b>	
Wi-Fi	No
Ethernet LAN	Yes
<b>Ports &amp; interfaces</b>	
USB 2.0 ports quantity	1
RS-232 ports	1
Optional connectivity	Serial (RS-232),USB 2.0
Connectivity technology	Wired
Wi-Fi	No
Ethernet LAN	Yes
<b>Paper handling</b>	
Media thickness	0.058 - 0.25 mm
<b>Performance</b>	
Built-in barcodes	Code 11,Code 128 (A/B/C),Code 39,Code 93,Data

	Matrix,EAN13,EAN8,MaxiCode,QR Code,TLC39,UPC-A,UPC-E
Ribbon width	11 cm
Ribbon length	450 m
Energy Star certified	Yes
<b>Power</b>	
Energy Star certified	Yes
<b>Technical details</b>	
Product colour	Black,Grey
Built-in barcodes	Code 11,Code 128 (A/B/C),Code 39,Code 93,Data Matrix,EAN13,EAN8,MaxiCode,QR Code,TLC39,UPC-A,UPC-E
Ribbon width	11 cm
Ribbon length	450 m
<b>Certificates</b>	
Energy Star certified	Yes
<b>Operational conditions</b>	
Storage temperature (T-T)	-40 - 60 °C
Storage relative humidity (H-H)	5 - 85%
Operating temperature (T-T)	5 - 40 °C
Operating relative humidity (H-H)	20 - 85%
<b>Weight &amp; dimensions</b>	
Width	269 mm
Depth	495 mm
Height	324 mm
Weight	16.3 kg