

Canon ImagePROGRAF TX-4000Specs

Printer

Printing Technology Inkjet

Ink Type Pigment Based

Ink Color
1 x Black
1 x Matte Black
1 x Cyan
1 x Magenta
1 x Yellow

Compatible Ink Cartridges Canon PFI-110, Canon PFI-310, Canon PFI-710

Number of Cartridges 5 Individual Cartridges

Number of Nozzles
5120 Nozzles (Matte Black)
2560 Nozzles (Per Other Color)
15,360 Nozzles (Total)

Print Resolution 2400 x 1200 dpi

Borderless Printing Yes

Line Accuracy $\pm 0.1\%$

Minimum Ink Droplet Size 5 pL

Printhead Swath	1.1" / 2.7 cm
Printer Language	HP-GL/2, HP-RTL, JPEG, PDF, SG Raster

Media Handling

Paper Handling	Media Cutter, Roll Feed
Media Roll Diameter	2" / 5.1 cm (Core) 3" / 7.6 cm (Core) 6.7" / 17 cm (Outer)
Media Length	59.0' / 18.0 m (Roll) 63.0" / 1.6 m (Sheet)
Media Width	8.0 to 44.0" / 20.3 to 111.8 cm
Media Thickness	2.8 to 31.4 mil / 0.1 to 0.8 mm

Connectivity

Interface	USB 2.0, Wi-Fi, Ethernet
Controller	L-COA PRO
Direct Printing	Apple AirPrint, USB Port
Hard Drive	500 GB
Memory	2 GB

Operating System Support	Windows, macOS/OS X
--------------------------	---------------------

Environmental

Operating Temperature	59 to 86°F / 15 to 30°C
-----------------------	-------------------------

Operating Humidity	10 to 80%
--------------------	-----------

General

Control Panel	<i>None</i>
---------------	-------------

AC Input Power	100 to 240 VAC, 50 / 60 Hz
----------------	----------------------------

Power Consumption	107 W (Maximum) 3.6 W (Standby) 0.3 W (Off)
-------------------	---

Max Acoustic Noise	6.9 BA (Power)
--------------------	----------------

Dimensions (W x H x D)	62.7 x 46.0 x 46.8" / 159.3 x 116.8 x 118.9 cm (with Basket Open, with Stand)
------------------------	---

Weight	277.0 lb / 125.6 kg (with Stand, with Stacker)
--------	--
